

Product data sheet

Characteristics

8910DPA72V09

Contactor, Definite Purpose, 75A, 2 pole,
15HP at 230VAC, 1 phase, 208/240VAC 60Hz
220VAC 50Hz coil, open



Main

Product or Component Type	Definite Purpose Contactor
Line Rated Current	75 A
Number of Poles	2P
Pole contact composition	2 NO
Range of Product	DPA

Complementary

Maximum Horse Power Rating	5 Hp 115 V AC, 1 phase 15 hp 230 V AC, 1 phase
Locked rotor rated current	450 A 277 V AC 375 A 460 V AC 300 A 575 V AC
[Ue] rated operational voltage	600 V AC
[Uc] control circuit voltage	208...240 V AC 60 Hz 220 V AC 50 Hz
Phase	1 phase
Electrical Connection	Quick connect terminals Box lugs

Environment

Product Certifications	UL Recognized[RETURN]CSA
------------------------	--------------------------

Ordering and shipping details

Category	21347-8910 DPA 7_(70 AMP)
Discount Schedule	CP1B
GTIN	785901177340
Returnability	No
Country of origin	CN

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.60 in (14.224 cm)
Package 1 Width	5.50 in (13.97 cm)
Package 1 Length	7.20 in (18.288 cm)
Package 1 Weight	3.39 lb(US) (1.538 kg)

Offer Sustainability

REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes

Contractual warranty

Warranty	18 months
----------	-----------