

Support Grips

Bus-Drop Single Eye and Locking Bale/Universal Eye

Grips



Features and Benefits

- Bus drop single eye/bale or locking/universal eye are used for bus drop cable
- Locking bale provides easy, quick attachment to fixed structure without the need for additional hardware
- Closed mesh top-mounted reinforced eye protector provides stable and longer-life support
- Galvanized Steel wire mesh is for indoor use only
- Stainless Steel is for indoor or outdoor use

Reference Information

UL File No. E76954 (except locking bale grips and accessories)

CSA File No.: LR32159 (except accessories)



Physical

Mesh Material: Galvanized Steel or Stainless Steel wire mesh

Weave Type: Single weave mesh

Mesh Type: Closed

Single Eye, Galvanized Steel

| Cable Diameter | Bale Length | Mesh Length | Approximate Break Strength* | Woodhead No. | Order No. |
|---------------------------|----------------|-----------------|-----------------------------|--------------|-------------|
| 5.59–8.13mm (.22–.32") | 0.229m (9.00") | 0.089m (3.50") | 650 lb | 36560 | 130094-0489 |
| 7.62–10.92mm (.30–.43") | 0.229m (9.00") | 0.114m (4.50") | 1100 lb | 36562 | 130094-0491 |
| 10.16–14.22mm (.40–.56") | 0.229m (9.00") | 0.127m (5.00") | 1100 lb | 36564 | 130094-0493 |
| 13.46–18.54mm (.53–.73") | 0.229m (9.00") | 0.165m (6.50") | 1100 lb | 36567 | 130094-0495 |
| 17.78–21.59mm (.70–.85") | 0.229m (9.00") | 0.216m (8.50") | 1900 lb | 36569 | 130094-0497 |
| 20.83–25.40mm (.82–1.00") | 0.229m (9.00") | 0.216m (8.50") | 1900 lb | 36571 | 130094-0499 |
| 24.38–31.75mm (.96–1.25") | 0.229m (9.00") | 0.279m (11.00") | 1900 lb | 36574 | 130094-0502 |

UL listed

* To determine Workload Safety Factor, divide Approximate Break Strength by 10. See technical section for break strength.

Single Eye, Stainless Steel

| Cable Diameter | Bale Length | Mesh Length | Approximate Break Strength* | Woodhead No. | Order No. |
|---------------------------|----------------|-----------------|-----------------------------|--------------|-------------|
| 5.59–8.13mm (.22–.32") | 0.229m (9.00") | 0.089m (3.50") | 650 lb | 36560SS | 130094-0490 |
| 7.62–10.92mm (.30–.43") | 0.229m (9.00") | 0.114m (4.50") | 1100 lb | 36562SS | 130094-0492 |
| 10.16–14.22mm (.40–.56") | 0.229m (9.00") | 0.127m (5.00") | 1100 lb | 36564SS | 130094-0494 |
| 13.46–18.54mm (.53–.73") | 0.229m (9.00") | 0.165m (6.50") | 1100 lb | 36567SS | 130094-0496 |
| 17.78–21.59mm (.70–.85") | 0.229m (9.00") | 0.216m (8.50") | 1900 lb | 36569SS | 130094-0498 |
| 20.83–25.40mm (.82–1.00") | 0.229m (9.00") | 0.216m (8.50") | 1900 lb | 36571SS | 130094-0500 |
| 24.38–31.75mm (.96–1.25") | 0.229m (9.00") | 0.279m (11.00") | 1900 lb | 36574SS | 130094-0503 |

UL listed

* To determine Workload Safety Factor, divide Approximate Break Strength by 10. See technical section for break strength.



Locking Bale/Universal Eye, Galvanized Steel

| Cable Diameter | Bale Length | Mesh Length | Approximate Break Strength* | Woodhead No. | Order No. |
|---------------------------|-----------------|-----------------|-----------------------------|--------------|-------------|
| 5.59–8.13mm (.22–.32") | 0.305m (12.00") | 0.089m (3.50") | 1100 lb | 36580 | 130094-0510 |
| 7.62–10.92mm (.30–.43") | 0.305m (12.00") | 0.114m (4.50") | 1100 lb | 36582 | 130094-0512 |
| 10.16–14.22mm (.40–.56") | 0.305m (12.00") | 0.127m (5.00") | 1100 lb | 36584 | 130094-0514 |
| 13.46–18.54mm (.53–.73") | 0.380m (15.00") | 0.165m (6.50") | 1100 lb | 36587 | 130094-0517 |
| 17.78–21.59mm (.70–.85") | 0.406m (16.00") | 0.216m (8.50") | 1900 lb | 36589 | 130094-0519 |
| 20.83–25.40mm (.82–1.00") | 0.406m (16.00") | 0.216m (8.50") | 1900 lb | 36591 | 130094-0520 |
| 24.38–31.75mm (.96–1.25") | 0.432m (17.00") | 0.279m (11.00") | 1900 lb | 36594 | 130094-0521 |

* To determine Workload Safety Factor, divide Approximate Break Strength by 10. See technical section for break strength.



Bus-Drop Accessories

| Description | Load (max.) | Galvanized Steel | | Stainless Steel | |
|---------------|-------------|------------------|-------------|-----------------|-------------|
| | | Woodhead No. | Order No. | Woodhead No. | Order No. |
| Safety spring | 40 lb | 36237 | 130099-0051 | 36237SS | 130099-0228 |
| Safety spring | 80 lb | 36238 | 130099-0052 | 36238SS | 130099-0229 |
| Support hook | | 36241 | 130094-0488 | 36241SS | 130094-1401 |