


Product data sheet

Characteristics

XZCC23MCM190S

male, M23, 19-pin, elbowed connector - cable gland Pg 13.5



Main

Accessory / separate part category	Cabling accessories
Accessory / separate part type	Connector
Electrical connection	Elbowed male connector M23, 19 pins
Collar material	Metal
Status LED	Without
Cable connection	Solder terminal 0.00 in ² (1 mm ²) 0.35...0.47 in (9...12 mm)

Complementary

Cable gland type	Pg 13.5
Cable connector fixing	Screw-on
[Ue] rated operational voltage	60 V AC 75 V DC
[In] rated current	7.5 A
Enclosure material	Metal
Minimum insulating resistance	10000000 GΩ
Contact resistance	5000 μOhm
Net weight	0.33 lb(US) (0.15 kg)

Environment

IP degree of protection	IP65
Ambient air temperature for operation	-13...230 °F (-25...110 °C)

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	5.93 oz (168 g)
Package 1 Height	0.98 in (2.5 cm)
Package 1 width	1.97 in (5 cm)
Package 1 Length	3.15 in (8 cm)
Unit Type of Package 2	S02

Number of Units in Package 2	50
Package 2 Weight	19.57 lb(US) (8.876 kg)
Package 2 Height	5.91 in (15 cm)
Package 2 width	11.81 in (30 cm)
Package 2 Length	15.75 in (40 cm)


Offer Sustainability

REACH Regulation	REACH Declaration
EU RoHS Directive	Not applicable, out of EU RoHS legal scope

Contractual warranty

Warranty	18 months
----------	-----------

Dimensions



(1) Cable gland: no. 13 metal (Pg 13.5)

Connections and Schemes

