

Product data sheet

Specifications



auxiliary latch block TeSys Deca - 220...240 V DC/AC 50...60 Hz

LA6DK10M

Product availability: Non-Stock - Not normally stocked in distribution facility

⚠ Discontinued

Main

Range	TeSys
Product or Component Type	Mechanical latch block
Product compatibility	LC1D40 3 phases + neutral AC LP1D40 3 phases + neutral DC LP1D65 3 phases + neutral DC LC1D65 3 phases + neutral AC
[Uc] control circuit voltage	220/240 V AC 50/60 Hz 220/240 V DC

Complementary

Mounting Location	Front side
Tripping control	Electrical Manual
[Ui] rated insulation voltage	690 V IEC 60947-5-1
Power required in VA	25 AC
Power required in W	30 W DC
Mechanical durability	500000 cycles
Maximum operating rate	1200 cyc/h
On-load factor	10 %
Product Weight	0.15 lb(US) (0.07 kg)

Environment

Product Certifications	CSA UL
IP degree of protection	IP2XVDE 0106
Protective treatment	THIEC 60068
Ambient Air Temperature for Operation	-13...131 °F (-25...55 °C)
Ambient Air Temperature for Storage	-40...176 °F (-40...80 °C)

Ordering and shipping details

Category	US10I1222341
Discount Schedule	0I12
GTIN	3389110745801
Returnability	No

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	1.811 in (4.600 cm)
Package 1 Width	2.559 in (6.500 cm)
Package 1 Length	1.969 in (5.000 cm)
Package weight(Lbs)	3.457 oz (98.000 g)
Unit Type of Package 2	S01
Number of Units in Package 2	32
Package 2 Height	5.906 in (15.000 cm)
Package 2 Width	5.906 in (15.000 cm)
Package 2 Length	15.748 in (40.000 cm)
Package 2 Weight	7.399 lb(US) (3.356 kg)

Contractual warranty

Warranty (in months)	18
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Total lifecycle Carbon footprint	4 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	0.6 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	0 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	3 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	0.2 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile

Use Better



Materials and Substances

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	Yes
SCIP Number	C7b64c73-e428-45b0-a9eb-af38721e12df
EU RoHS Directive	Compliant By Exemption
REACH Regulation	Reference contains Substances of Very High Concern above the threshold

Use Longer



Lifetime extension

Repair	No
--------	----

Use Again



Repack and remanufacture

Recyclability potential, in %	49
Circularity Profile	End of Life Information
Take-back	No
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.