

GS1AM1

Auxiliary contacts, TeSys GS, 1 C/O, early break, front mounting, for GS1 50 to 400A with direct right handle



Main

Range of Product	TeSys
Device short name	GS1AM
Product or Component Type	Auxiliary contact
Contact application	O and I position signalling
Range compatibility	TeSys TeSys GS GS1 F fuse-switch disconnecter TeSys TeSys GS GS1G fuse-switch disconnecter TeSys TeSys GS GS1 J fuse-switch disconnecter TeSys TeSys GS GS1 K fuse-switch disconnecter TeSys TeSys GS GS1 L fuse-switch disconnecter TeSys TeSys GS GS1 N fuse-switch disconnecter TeSys TeSys GS GS1Q fuse-switch disconnecter
Contacts type and composition	1 C/O
Contact operation	Early-break
[I _{th}] conventional free air thermal current	16 A (at 104 °F (40 °C))
[I _e] rated operational current	5 A 127 V AC-15 4 A 230 V AC-15 3 A 400/415 V AC-15 2 A 440 V AC-15 12 A 24 V DC-13 2 A 48 V DC-13 0.6 A 110 V DC-13 0.4 A 220 V DC-13

Complementary

Mechanical durability	1 Mcycles
Electrical durability	30000 cycles AC-15
Switch rated current	50 A 63 A 100 A 125 A 160 A 200 A 250 A 315 A 400 A
Fuse type	NFC DIN BS
Type of operating handle	Direct right side
Mounting Location	Front face
Net Weight	0.05 lb(US) (0.023 kg)

Ordering and shipping details

Category	18402-WORLD SERVICE PARTS(CONTROL ACCESS)
Discount Schedule	CP10
GTIN	3389110563214
Returnability	No
Country of origin	FR

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	0.98 in (2.5 cm)
Package 1 Width	3.74 in (9.5 cm)
Package 1 Length	4.33 in (11.0 cm)
Package 1 Weight	0.85 oz (24.0 g)
Unit Type of Package 2	S02
Number of Units in Package 2	60
Package 2 Height	5.91 in (15.0 cm)
Package 2 Width	11.81 in (30.0 cm)
Package 2 Length	15.75 in (40.0 cm)
Package 2 Weight	4.18 lb(US) (1.895 kg)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Styrene, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Contractual warranty

Warranty	18 months
----------	-----------