



Main

Range of Product	PacDrive 3
Product or Component Type	Cable

Complementary

Range Compatibility	Lexium 62 Lexium 52
Product compatibility	LXM 62 servo drive LXM 52 servo drive SH31403P... SH31404P... SH32051P... MH31403P... MH31901P...
Connector type	M40
Accessory / separate part destination	Holding brake Temperature sensor Power supply
Cable cross section	0.00 in ² (2.5 mm ²)
Cable length	131.23 ft (40 m)
Net Weight	28.78 lb(US) (13.055 kg)

Ordering and shipping details

Category	18353-PACDRIVE3 ACCESSORIES
Discount Schedule	PC52
GTIN	3606485287959
Returnability	No
Country of origin	DE

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.67 in (14.4 cm)
Package 1 Width	28.54 in (72.5 cm)
Package 1 Length	28.54 in (72.5 cm)
Package 1 Weight	28.78 lb(US) (13.055 kg)

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information

Contractual warranty

Warranty	18 months
----------	-----------