



ILSCON® Splices Insulated



- Butted configuration
- Internal wire stops
- Color coded
- Funnel wire entry
- Seamless barrel - VBSS, NBSS
- Vinyl insulation - VBST, VBSS
- Nylon insulation - NBSS
- Manufactured from high strength copper alloy
- UL Listed
- Provides fast, easy wire insertion in limited space applications, simply strip and crimp
- Ensures proper insertion length
- Provide easy wire range identification
#18-22 AWG Red
#14-16 AWG Blue
#10-12 AWG Yellow
- Offers maximum conductivity
- Provides low contact resistance
- Smooth wire insertion into barrel
- Maximum crimp connection to prevent wire pull-out
- Provides corrosion resistance and strain relief
- Increased heat and chemical resistant qualities for more demanding applications
- Ensures reliability for copper conductor

</>All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)
Tested to UL 486A/B, UL File E6207</>

Item ID	Conductor Range	Voltage	Temperature Rating	Length	Installation Tooling ILST-22K	Package Quantity
VBSS-18-P50	18-22	600 V	75°C	0.953	Die Set A	50



ILSCON® Splices Insulated

Item ID	Conductor Range	Voltage	Temperature Rating	Length	Installation Tooling ILST-22K	Package Quantity
VBSS-14-P50	14-16	600 V	75°C	0.953	Die Set A	50
VBSS-10-P25	10-12	600 V	75°C	1.024	Die Set A	25