



H: 2 5/8" (66.5 mm)
Ø: 1 1/4" (32 mm)

Figure A



H: 2 5/16" (59 mm)
Ø: 1 3/8" (35 mm)

Figure B



H: 2 1/2" (63.5 mm)
Ø: 1 1/4" (32 mm)

Figure C

Order code	Description	Watts (W)	Circuit	ANSI code	Distance ballast to lamp (ft.)	Case temperature (°C)	Case shape	Figure
16654	IGN35150HPS/R/QC/B	35	R	S76	2	105	Round	A
		50	R	S68	2	105	Round	
		70	R	S62	2	105	Round	
		100	R	S54	2	105	Round	
		150	R	S55	2	105	Round	
62987	IGN35150HPS/H/STD	35	R	S76	2	105	Round	B
		50	H	S68	10	105	Round	
		50	R	S68	2	105	Round	
		70	H	S62	10	105	Round	
		70	R	S62	2	105	Round	
		100	H	S54	10	105	Round	
		100	R	S54	2	105	Round	
		150	H	S55	10	105	Round	
		150	R	S55	2	105	Round	
16651	IGN50150HPS/LI/H/QC/B	50	CWI	S68	12	105	Round	A
		70	CWI	S62	12	105	Round	
		100	CWI	S54	12	105	Round	
		150	CWI	S55	3	105	Round	
16647	IGN150430HPS/A/LR/A	150	CWA	S56	50	105	Round	C
		150	R	S56	50	105	Round	
		200	CWA	S66	50	105	Round	
		200	CWA	S66	50	105	Round	
		200	R	S66	50	105	Round	
		250	CWA	S50	50	105	Round	
		250	R	S50	50	105	Round	
		250	CWA	S50	50	105	Round	
		310	CWA	S67	50	105	Round	
		310	R	S67	50	105	Round	
		400	CWA	S51	50	105	Round	
		400	R	S51	50	105	Round	
		430	CWI	S145	35	105	Round	

07

