



Main

Product or component type	Plug-in unit
Range of product	I-Line
Circuit breaker type	M-frame
Trip unit technology	Electronic, basic, ET 1.0, LI

Complementary

Protection type	Circuit breaker
Mounting mode	Bolt-on
[Ue] rated operational voltage	600 V AC
[In] rated current	400 A
Number of Phases	3 phases
Poles description	3P
Interrupt Rating	65 kA 240 V AC 35 kA 480 V AC 18 kA 600 V AC
[Ics] rated service short-circuit breaking capacity	80 %
Wiring configuration	4-wire (integral ground bus)
AWG gauge	AWG 3/0...500 kcmil 3 phase and neutral AWG 6...300 kcmil 4 ground
Depth	20.24 in (514 mm)
Height	46.22 in (1174 mm)
Width	22.99 in (584 mm)
Condition of use	Vertical installation

Environment

Product certifications	UL listed file E22182
------------------------	-----------------------

Standards	UL 857
-----------	--------

Packing Units

Package 1 Weight	284.00 lb(US) (128.820 kg)
------------------	----------------------------

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile
