

# Product data sheet

## Characteristics

# VW3M8221R1000

cable for creating control cord sets for encoders- 5x(2x0.25mm<sup>2</sup>)+(2x0.5mm<sup>2</sup>)-100m



### Main

Range of Product	Lexium
Accessory / separate part category	Connection accessory
Accessory / separate part type	Control cable
Product or Component Type	Feedback cable
Device Application	For creating control cordsets for SinCos Hiperface encoders
Accessory / separate part destination	From servo motor to servo drive
Cable composition	5 x (2 x 0.25 mm <sup>2</sup> ) + (2 x 0.5 mm <sup>2</sup> )

### Complementary

Range Compatibility	Lexium 15 Lexium 32 Altivar Machine ATV340 Altivar&Nbsp;Process ATV900 Lexium 05
Cable length	328.08 ft (100 m)
Net Weight	46.30 lb(US) (21 kg)

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	7.87 in (20.0 cm)
Package 1 Width	29.53 in (75.0 cm)
Package 1 Length	29.53 in (75.0 cm)
Package 1 Weight	46.30 lb(US) (21.0 kg)

### Offer Sustainability

REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
RoHS exemption information	<a href="#">Yes</a>
PVC free	Yes

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.