

Product data sheet

Characteristics

8538SEA23V02S

NEMA combination starter, Type S, 100A fusible disconnect, Size 3, 90A, 50HP at 600VAC, 3 phase, 3 pole, melting alloy, 120VAC coil, NEMA 12



Main

| | |
|----------------------|--------------------------|
| Product | Combination Starter |
| Type | S |
| Control Circuit Type | Separate control circuit |

Complementary

| | |
|-------------------------|--|
| Control Circuit Voltage | 110 V AC 50 Hz 120 V AC 60 Hz |
| Starter Type | Non reversing |
| Number of Poles | 3P |
| Horsepower Rating | 50 Hp 460 V AC, 3 phase 50 hp 575 V AC, 3 phase |
| Maximum Voltage Rating | 600 V AC |
| Control Units | No control units |
| Pilot Light | No indicator |
| Auxiliary Contacts | Without |
| Thermal overload type | Melting alloy 3 |
| Disconnect Type | Fusible disconnect switch H, 100 A |
| NEMA size | 3 |

Environment

| | |
|----------------|---|
| Enclosure Type | NEMA 12 painted sheet steel with external reset |
|----------------|---|

Ordering and shipping details

| | |
|-------------------|----------------------------------|
| Category | 21214-8538,39 SE,SF(NOT S*R,T,W) |
| Discount Schedule | CP1 |
| GTIN | 785901458944 |
| Returnability | No |
| Country of origin | MX |

Packing Units

| | |
|------------------------------|---------------------------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 18.30 in (46.482 cm) |
| Package 1 Width | 13.70 in (34.798 cm) |
| Package 1 Length | 37.20 in (94.488 cm) |
| Package 1 Weight | 112.00 lb(US) (50.802 kg) |

Offer Sustainability

| | |
|---------------------------|---|
| California proposition 65 | WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov |
| REACH Regulation | REACH Declaration |
| EU RoHS Directive | Not compliant |
| China RoHS Regulation | China RoHS Declaration |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|