

OVC Compact Electronic Fan Heater



VERSION AVAILABLE



Features

Color

- Standard: white.
- Optional (upcharge applicable): almond, metallic silver, bronze, metallic charcoal, aluminum, semi-gloss black, sand.
- Custom colors available upon request.

Finish

- Standard: epoxy/polyester powder paint.

Voltage

- 240/208V, 1-phase.

Construction

- Shock-resistant cast aluminum front cover.
- 20-gauge steel.
- High-limit temperature control with automatic reset.

Fan

- Whisper-quiet squirrel-cage fan.
- Factory-lubricated, two-speed motor.

Heating element

- Nickel-chromium alloy stitched wire protected by mica insulators.
- Heating element provides instant heat.

Control

Model (-TH)

- Operating modes adapted for all requirements (comfort, economy, frost-free mode).

- Built-in electronic digital thermostat/timer with backlit display that can be used as a night light.
- Electronic thermostat with 2 triacs automatically switches from 750W to 1500W when needed.
- Keypad lock function that eliminates unwanted temperature adjustments and the use of the thermostat modes.

Model (-PW)

- Requires non pulsing wall-mounted thermostat (sold separately).
- Wattage must be selected at the time of wiring (750W or 1500W).

Installation

- 6 in. (152 mm) minimum clearance to floor.
- May be recessed or surface-mounted without adaptor in 2 in. X 3 in. stud partitions with gypsum.
- Easy installation and connection with mounting screws and knockouts (mounting screws included).
- Template included.

Warranty

- 5-year warranty against defects.

Application

- Hallways, bathrooms, shower rooms, dining rooms, kitchens, corridors.

Models

Watts		Volts	Product #	Price	Weight	
min.	max.				lb	kg
750/563	1500/1125	240/208	OVC1500BL-TH	422.00	11.5	5.22
750/563	1500/1125	240/208	OVC1500BL-PW ¹	341.00	12.2	5.53

Options

Product # Factory # installed*	Price	Description
DIS ²	112.00	Disconnect switch, 20A at 250V
R ³	77.00	Single-pole relay, coil 24V, without transformer, 22A at 208V, 240V
RT ³	105.00	Single-pole relay, coil 24V, with transformer 208V, 240V/24V, 22A max.
TRIAC ³	77.00	Single-pole electronic relay, coil 24V, without transformer, 15A at 240V max.
TRIAC ³	105.00	Single-pole electronic relay, coil 24V, with transformer, 15A at 240V max.

* For factory installed options, add the option number to the product number. See the **Product Code** section inside the front cover.

¹ Requires non pulsing wall-mounted thermostat (sold separately). Please refer to the Wall Thermostats Reference Chart.

² For the U.S. only: The nominal current of the unit must not exceed 80% of the capacity of the disconnect. This option is available with built-in thermostat (option -TH) or power selector (option -PW).

³ These options must be chosen with the power selector (option -PW).

Custom colors available upon request.

