

Product Number: 21364

Order Abbreviation: F4T5/CW

General Description: 4W, preheat fluorescent lamp, Cool White phosphor, 4200K color temperature, 60 CRI. 6000 Avg rated life at 3 hrs/start



Product Information

Abbrev. With Packaging Info.	F4T5CW 25/CS 1/SKU
Actual Length (in)	5.909
Actual Length (mm)	150.09
Average Rated Life (hr)	6000
Base	Miniature Bipin
Bulb	T5
Color Rendering Index (CRI)	60
Color Temperature/CCT (K)	4000
Diameter (in)	0.630
Diameter (mm)	16.00
Initial Lumens at 25C	140
Nominal Length (in)	6.000
Nominal Length (mm)	152.40
Nominal Wattage (W)	4.50

Footnotes

- Approximate initial lumens after 100 hours operation.
- The life ratings of fluorescent lamps are based on 3 hr. operating cycles under specified conditions and with ballast meeting ANSI specifications. If operating cycle is increased, there will be a corresponding increase in the average hours life.
- Minimum starting temperature is a function of the ballast; consult the ballast manufacturer.
- Preheat lamp, starter required.
- Mean lumens are measured at 40% of average rated lamp life.
- The lamp should not be in contact with any surface of the luminaire (applies to either high frequency or 60Hz ballasted systems).