

SFX 11/60 MM GE**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

**Highly flexible: SFX**

SFX markers are the preferred choice for labelling cables if you prefer the classic cable tie solution. Cables do not always run in a straight line. The material used in SFX markers addresses this fact with highly flexible polyurethane. The marker follows each curve of the cable and latches on with ease.

General ordering data

| | |
|--------------------|---|
| Version | SlimFix, Conductor and cable markers, 7 -, 60 x 13 mm, yellow |
| Order No. | 2005400000 |
| Type | SFX 11/60 MM GE |
| GTIN (EAN) | 4050118390209 |
| Qty. | 1,000 pc(s). |
| compatible printer | 2599430000 2599440000 |

Creation date November 26, 2024 12:29:37 PM CET

Catalogue status 26.11.2024 / We reserve the right to make technical changes.

SFX 11/60 MM GE

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Dimensions and weights

| | | | |
|------------|---------|-----------------|------------|
| Depth | 0.6 mm | Depth (inches) | 0.024 inch |
| Height | 60 mm | Height (inches) | 2.362 inch |
| Width | 13 mm | Width (inches) | 0.512 inch |
| Net weight | 0.566 g | | |

Temperatures

| | |
|-----------------------------|-------------|
| Operating temperature range | -40...90 °C |
|-----------------------------|-------------|

General data

| | | | |
|-----------------------------------|--------------|-----------------------------------|--------------|
| Colour | yellow | Halogen | No |
| Material | Polyurethane | Number per roll | 1,000 |
| Operating temperature range | -40...90 °C | Operating temperature range, max. | 90 °C |
| Operating temperature range, min. | -40 °C | Size of labelling field | 44 x 10.5 mm |
| UL 94 flammability rating | HB | Version | halogen-free |
| Width | 13 mm | | |

Conductor and cable markers

| | | | |
|----------------------|---------|-------------------|---------|
| Cable tie passage | Flat | Conductor O.D. | 7 - |
| Conductor O.D., min. | 7 mm | Halogen | No |
| Suitable cable tie | Plastic | Text field height | 10.5 mm |
| Text field width | 44 mm | | |

Classifications

| | | | |
|-------------|-------------|-------------|-------------|
| ETIM 6.0 | EC001530 | ETIM 7.0 | EC001530 |
| ETIM 8.0 | EC001530 | ETIM 9.0 | EC001530 |
| ECLASS 9.0 | 27-40-04-01 | ECLASS 9.1 | 27-40-04-01 |
| ECLASS 10.0 | 27-40-04-01 | ECLASS 11.0 | 27-28-11-02 |
| ECLASS 12.0 | 27-28-11-02 | ECLASS 13.0 | 27-28-11-02 |
| ECLASS 14.0 | 27-28-11-02 | | |

Environmental Product Compliance

| | |
|------------------------|-----------------------------|
| RoHS Compliance Status | Compliant without exemption |
| REACH SVHC | No SVHC above 0.1 wt% |

Approvals

| | |
|------|---------|
| ROHS | Conform |
|------|---------|

Downloads

| | |
|------------------|--|
| Engineering Data | CAD data – STEP |
| Catalogues | Catalogues in PDF-format |

Data sheet

SFX 11/60 MM GE

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany

www.weidmueller.com

Drawings

