



### Main

Range	Multi9
Product name	Multi9 PRD1
Product or Component Type	Surge arrester
Device short name	PRD1 75r
Poles description	1P
Remote signalling	With
Signal contacts composition	1 SD (1 C/O)
Surge arrester type	Electrical distribution network

### Complementary

Surge arrester class type	Type 1
Surge arrester technology	MOV
Wiring configuration	2-wire
Nominal discharge current	Common mode 20 kA L/PE)
Maximum discharge current	75 kA
[Iimp] impulse current	75 kA
[Uc] maximum continuous operating voltage	Common mode 175 V AC L/N
Maximum [Up] voltage protection level	<600 V L/N
Disconnecter device type	Associated circuit breaker 30 A C 14 kA
Short-circuit withstand	200 kA
Local signalling	Green mechanical indicator operating Red mechanical indicator end of life
Mounting Mode	Clip-on
Mounting Support	DIN rail
9 mm pitches	2
Height	3.61 in (91.7 mm)
Width	0.69 in (17.5 mm)
Depth	2.81 in (71.4 mm)
Net Weight	5.43 oz (154 g)
Color	Gray RAL 7035)
Response Time	< 25 ns
Connections - terminals	Tunnel type terminal 0.01...0.05 in <sup>2</sup> (6...35 mm <sup>2</sup> ) AWG 10...AWG 2) - rigid Tunnel type terminal 0.01...0.04 in <sup>2</sup> (6...25 mm <sup>2</sup> ) AWG 10...AWG 4) - flexible Tunnel type terminal dry contacts) 0.00...0.00 in <sup>2</sup> (0.5...1.5 mm <sup>2</sup> )
Wire stripping length	0.39 in (10 mm) for L/N connection 0.39 in (10 mm) for PE connection 0.24 in (6 mm) for dry contacts connection
Tightening torque	26.55 Lbf.in (3 N.m) L/N 26.55 lbf.in (3 N.m) PE

### Environment

Standards	UL 1449:ed. 4
IP degree of protection	Built-in NEMA 1
Pollution degree	3
Relative humidity	0...95 %
Operating altitude	6561.68 ft (2000 m)

Ambient Air Temperature for Operation	-13...140 °F (-25...60 °C)
Ambient Air Temperature for Storage	-40...185 °F (-40...85 °C)

## Ordering and shipping details

Category	08468-SURGE PROTECTION OEM
Discount Schedule	DE1B
GTIN	3606485010199
Returnability	Yes

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	1.10 in (2.8 cm)
Package 1 Width	3.62 in (9.2 cm)
Package 1 Length	4.80 in (12.2 cm)
Package 1 Weight	5.50 oz (156.0 g)
Unit Type of Package 2	S02
Number of Units in Package 2	40
Package 2 Height	5.91 in (15.0 cm)
Package 2 Width	11.81 in (30.0 cm)
Package 2 Length	15.75 in (40.0 cm)
Package 2 Weight	14.57 lb(US) (6.608 kg)

## Offer Sustainability

REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
RoHS exemption information	<a href="#">Yes</a>
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.