

Product data sheet

Characteristics

9070T5000D33

Transformer, Type T, industrial control,
5000VA, 1 phase, 380/400/415V primary,
115/230V secondary, 115C rise



Main

Product Type	Industrial Control Transformer
Type	T

Complementary

Number of Phases	1 phase
Power Rating	5000 VA UL[RETURN]5000 VA CSA[RETURN]5000 VA NOM[RETURN]3000 VA CE
Primary to Secondary Voltage	380/400/415 V 115/230 V
Temperature Rise	115 °C
Electrical Connection	Screw clamp terminals
Height	8.75 in (222.25 mm)
Width	9 in (228.60 mm)
Depth	9.15 in (232.41 mm)
Fingersafe Cover Compatibility	FSC2

Environment

Certifications	UL Listed[RETURN]cUL[RETURN]CSA
Enclosure Type	Not rated (open device)
Insulation Temperature	356 °F (180 °C)

Ordering and shipping details

Category	16205-9070 T (NOT TF) 3000 - 5000VA
Discount Schedule	CP8
GTIN	785901334385
Returnability	No
Country of origin	US

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	13.20 in (33.528 cm)
Package 1 Width	11.80 in (29.972 cm)
Package 1 Length	14.80 in (37.592 cm)
Package 1 Weight	95.40 lb(US) (43.273 kg)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Phenyl glycidyl ether, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations
PVC free	Yes

Contractual warranty

Warranty	18 months
----------	-----------