

EXTRA-HEAVY DUTY FIBERGLASS EXTENSION

Meets or exceeds CSA Grade 1A, ANSI Type 1A

- Durable non-conductive fiberglass side rails in high visibility safety yellow
- Rung through rail design
- Slip-resistant serrated "D" rungs for safe climbing and comfort
- Premium heavy duty rung locks for durability
- Black ABS, high impact non-marring end caps
- Large heavy duty pivot feet with slip-resistant rubber pads and ice pick

MODEL	SIZE	MAX. OPEN LENGTH	BASE SECTION		FLY SECTION		APPROX. WEIGHT lbs.
			OUTSIDE WIDTH	INSIDE WIDTH	OUTSIDE WIDTH	INSIDE WIDTH	
6916	16'	13'	17 1/8"	14 3/4"	16 1/8"	13 3/4"	34
6920	20'	17'	17 1/8"	14 3/4"	16 1/8"	13 3/4"	43
6924	24'	21'	17 1/8"	14 3/4"	16 1/8"	13 3/4"	51
6928	28'	25'	17 1/8"	14 3/4"	16 1/8"	13 3/4"	58
6932	32'	28'	17 1/8"	14 3/4"	16 1/8"	13 3/4"	65



HEAVY DUTY FIBERGLASS EXTENSION

Meets or exceeds CSA Grade 1, ANSI Type 1

- Durable non-conductive fiberglass side rails in high visibility safety orange
- Rung through rail design
- Slip-resistant serrated "D" rungs for safe climbing and comfort
- Premium heavy duty rung locks for durability
- Black ABS, high impact non-marring end caps
- Large heavy duty pivot feet with slip-resistant rubber pads and ice pick

MODEL	SIZE	MAX. OPEN LENGTH	BASE SECTION		FLY SECTION		APPROX. WEIGHT lbs.
			OUTSIDE WIDTH	INSIDE WIDTH	OUTSIDE WIDTH	INSIDE WIDTH	
6316	16'	13'	17 1/8"	14 3/4"	16 1/8"	13 3/4"	32
6320	20'	17'	17 1/8"	14 3/4"	16 1/8"	13 3/4"	38
6324	24'	21'	17 1/8"	14 3/4"	16 1/8"	13 3/4"	45



MEDIUM DUTY FIBERGLASS EXTENSION

Meets or exceeds CSA Grade 2, ANSI Type 2

- Durable non-conductive fiberglass side rails in high visibility safety red
- Rung through rail design
- Slip-resistant serrated "D" rungs for safe climbing
- Premium heavy duty rung locks for durability
- Black ABS, high impact non-marring end caps
- Large heavy duty pivot feet with slip-resistant rubber pads and ice pick

MODEL	SIZE	MAX. OPEN LENGTH	BASE SECTION		FLY SECTION		APPROX. WEIGHT lbs.
			OUTSIDE WIDTH	INSIDE WIDTH	OUTSIDE WIDTH	INSIDE WIDTH	
5816	16'	13'	17 1/8"	14 3/4"	16 1/8"	13 3/4"	28
5820	20'	17'	17 1/8"	14 3/4"	16 1/8"	13 3/4"	32
5824	24'	21'	17 1/8"	14 3/4"	16 1/8"	13 3/4"	38
5828	28'	25'	17 1/8"	14 3/4"	16 1/8"	13 3/4"	42

