# Product data sheet
## Characteristics

# PHL36040GN
## 40A 277/480 V H-Frame Electronic Trip Circuit Breaker Busway Plug-In Unit

## Main

| | |
|---|---|
| Product or component type | Section |

## Complementary

| | |
|---|---|
| Fixing mode | Plug-in |
| [Ue] rated operational voltage | 600 V AC 50/60 Hz<br>277/480 V AC 50/60 Hz |
| Network number of phases | 3 phases |
| Busbar description | Ground |
| Fuse type | H |
| Breaking capacity code | L |
| Disconnector device type | Associated circuit breaker 40 A 125 kA 240 V<br>Associated circuit breaker 40 A 100 kA 480 V<br>Associated circuit breaker 40 A 50 kA 600 V |
| Level or class | Class 5600 |
| Wiring configuration | 4-wire |

## Environment

| | |
|---|---|
| Product certifications | CSA<br>UL |

## Packing Units

| | |
|---|---|
| Package 1 Weight | 32.00 lb(US) (14.515 kg) |

## Offer Sustainability

| | |
|---|---|
| Sustainable offer status | Green Premium product |
| REACh Regulation | REACh Declaration |
| EU RoHS Directive | Compliant |

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

| | |
|---|---|
| | EU RoHS Declaration |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| China RoHS Regulation | China RoHS declaration<br>Product out of China RoHS scope. Substance declaration for your information |
| Environmental Disclosure | Product Environmental Profile |