Product data sheet
Characteristics

XZCR1511064D2
jumper cable XZ - male straight M12 5-pin - female straight M12 5-pin - PUR 2m

Main

Accessory / separate part category	Cabling accessory
Accessory / separate part type	Jumper cable

Complementary

Jumper cable end 1	M12 male 5 pins straight screw-on
Jumper cable end 2	M12 female 5 pins straight screw-on
Cable composition	4 x 0.34 mm² + 1 x 0.5 mm²
Cable length	6.56 ft (2 m)
Wire insulation material	PUR
Cable outer diameter	0.23 in (5.9 mm)
[Ue] rated operational voltage	30 V AC 36 V DC
[In] rated current	4 A
Insulation resistance	>= 1000 MOhm
Maximum resistance across terminals	5000 mOhm
Net weight	0.29 lb(US) (0.13 kg)

Environment

IP degree of protection	IP69K IP65 IP67
Product certifications	CULus
Ambient air temperature for operation	-31…194 °F (-35…90 °C) static 23…194 °F (-5…90 °C) flexing
Ambient air temperature for storage	-31…212 °F (-35…100 °C)

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	3.59 oz (101.9 g)
Package 1 Height	0.59 in (1.5 cm)
Package 1 width	9.45 in (24 cm)
Package 1 Length	9.45 in (24 cm)
Unit Type of Package 2	BAG
Number of Units in Package 2	1
Package 2 Weight	3.60 oz (102 g)
Package 2 Height	0.59 in (1.5 cm)
Package 2 width	9.45 in (24 cm)
Package 2 Length	9.45 in (24 cm)
Unit Type of Package 3	S02
Number of Units in Package 3	40
Package 3 Weight	9.62 lb(US) (4.362 kg)
Package 3 Height	5.91 in (15 cm)
Package 3 width	11.81 in (30 cm)
Package 3 Length	15.75 in (40 cm)

Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information

Contractual warranty

Warranty	18 months

XZCR1511064D2

Dimensions



L : Lenght of cable

XZCR1511064D2

Connections and Schemes