

## 2 STRIP LGX WALL MOUNT PATCH PANEL

---

PDS-0124



### DESCRIPTION

The 2 Strip LGX Wall Mount Patch Panel is designed for fiber interconnects and splicing while offering a discreet and low profile. The patch panel is made of 16 gauge cold rolled steel (CRS) with a black powder coated finish. Modular cassettes or adapter strips of 48 fibers can be installed into the 2 LGX cut-outs using their push pin mechanism. Four self-sealing grommets allow for multiple cable entrance and exits. This low profile patch panel features two separate doors which are lockable with key locks (not included, part number WW000014) to control access to the distribution or patch sides, providing additional network security.

**FEATURES  
and BENEFITS**

- Low profile design for space saving
- Fits 2 LGX adapter strips, and cassettes
- 4 grommets to limit contaminant intrusion at the cable entrance points
- Maximum capacity of 48 fiber
- Both doors are lockable to protect your network (key lock not included)
- Installation hardware and instruction manual included

**APPLICATIONS**

- Data Center
- Telecommunications Room
- Equipment Room
- Consolidation Point

**ORDERING  
INFORMATION**

Part Number	Description
PP-WM2S	2 Strip LGX Wall Mount Patch Panel - Empty

*Note: fully loaded solutions available. Please contact your local sales representative.*

**PACKAGING  
and SHIPPING**

Description
Cardboard box: 1 unit/box

**INCLUDED**

Hardware
4 x Wood screws 10" x 0.75" 2 x Nylon tie wraps 4 x Velcro tie wraps, 11.8" long 1 x Self-adhesive port ID label 1 x Warning label 1 x Instruction manual

**PHYSICAL  
SPECIFICATIONS**

Attribute	Value
Product Dimensions	15.625" x 13" x 2.125" (381.6 mm x 330.2 mm x 54 mm)
Panel Materials	16 gauge cold rolled steel (CRS)
Plastic Materials	UL 94V-0 thermoplastic
Color & Finish	Black Sandex
Fiber Count Capacity	48F (LC)

**MECHANICAL SPECIFICATIONS**

Attribute	Value
Installation Temperature	-25° C (-13° F) ~ 40° C (104° F)
Storage Temperature	-25° C (-13° F) ~ 55° C (131° F)
Relative Humidity	≤ 85% (30° C)

**STANDARDS COMPLIANCE**

**TIA-569-B**  
Commercial Building Standard for Telecommunications Pathways and Spaces

**UL 94**  
Tests for Flammability of Plastic Material for Parts in Devices and Appliances

**CEA/EIA-310-E**  
Cabinets, Racks, Panels and Associated Equipment Standard

**RoHS**  
Directive on Restriction of Hazardous Substances

**ANSI/TIA/EIA-606-A**  
Administration Standard for Telecommunications Infrastructure