

Product data sheet

Characteristics

9070SK3000G2D1G13

Transformer disconnect, 3000VA, 240x480VAC primary, 120VAC secondary, with outlet, Type 1

Main

Product	Transformer Disconnect
Certifications	CSA[RETURN]JUL Listed
Enclosure Type	NEMA 1 standard
Insulation Temperature	356 °F (180 °C)
Phase	1 phase
Primary Voltage	240 x 480 V
Power Rating	3000 VA
Secondary Voltage	120 V
Temperature Rise	115 °C
Electrical Connection	Screw clamp terminals
Type	SK

Ordering and shipping details

Category	21694-9070 SK
Discount Schedule	CP8
GTIN	785901284468
Returnability	No
Country of origin	US

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	16.30 in (41.402 cm)
Package 1 Width	18.50 in (46.99 cm)
Package 1 Length	24.60 in (62.484 cm)
Package 1 Weight	87.00 lb(US) (39.463 kg)

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Phenyl Glycidyl Ether, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
RECh Regulation	RECh Declaration
RECh free of SVHC	Yes
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes

Contractual warranty

Warranty	18 months
----------	-----------