



Figure A
H: 3.68" - 93.00 mm
Dia. : 1.62" - 41.00 mm



Figure B
H: 4.90" - 124.5 mm
Dia. : 1.80" - 46.00 mm



Figure C
H: 3.75" - 95.00 mm
Dia. : 1.50" - 38.00 mm



Figure D
H: 2.76" - 70.00 mm
Dia. : 1.62" - 41.00 mm



Figure E
H: 3.94" - 100.00 mm
Dia. : 1.97" - 50.00 mm



Figure F
H: 4.72" - 120.00 mm
Dia. : 1.80" - 46.00 mm

Pulse Start Metal Halide

Order code	Description	Microfarads (μf)	Voltage (V)	Case temperature ($^{\circ}\text{C}$)	Capacitor type	Contains PCB	Figure
16566	22MF 330VAC DRY CAPACITOR	22	330	100	Dry Film	No	A
16567	24MF 330VAC DRY CAPACITOR	24	330	100	Dry Film	No	A
31208	24MF 480VAC DRY CAPACITOR	24	480	100	Dry Film	No	B
31209	15MF 400VAC DRY CAPACITOR	15	400	100	Dry Film	No	C
31331	12MF 330VAC DRY CAPACITOR	12	330	100	Dry Film	No	D
58938	22MF 500VAC OIL CAPACITOR	22	500	100	Oil Filled	No	E
59553	26MF 400VAC DRY CAPACITOR	26	400	100	Dry Film	No	F
61037	28MF 480VAC OIL CAPACITOR	28	480	100	Oil Filled	No	E



Data is based upon tests performed in a controlled environment and representative of relative performance. Actual performance can vary depending on operating conditions. Specifications are subject to change without notice. June 19, 2014

