

# Product data sheet

## Characteristics

# CHOM1632L125B

Loadcentre, Homeline, 1 phase, 16 spaces, 32 circuits, 125A main lugs, Type 1, hub ready



### Main

Range of Product	Homeline
Product or Component Type	Load Center
Line Rated Current	125 A
[Ue] rated operational voltage	120/240 V AC
Mounting Mode	Wall mount
Short-circuit current	10 kA

### Complementary

Electrical Connection	Lugs
AWG gauge	AWG 6...AWG 2/0 aluminium/copper
Load center type	Main lugs
Number of spaces	16
Number of circuits	32
Number of tandem circuit breakers	16
Phase	1 phase
Cover type	Combination flush/surface cover
Device Composition	Grounding bar included (not installed)
Wiring configuration	3-wire
Material	Tin plated aluminium: busbar
Enclosure Material	Welded sheet steel
Cover colour	Grey
Box number	8
Height	26 in (660.40 mm)
Width	14.25 in (361.95 mm)
Depth	3.75 in (95.25 mm)

### Environment

Product Certifications	CSA
NEMA degree of protection	NEMA 1 indoor)
Ambient Air Temperature for Operation	23 °F (-5 °C) 104 °F (40 °C)

### Ordering and shipping details

Category	00199-DE5 MISC. SERVICE PARTS
Discount Schedule	DE5
GTIN	785901462347
Returnability	Yes

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	25.98 in (66.0 cm)
Package 1 Width	14.25 in (36.2 cm)
Package 1 Length	3.74 in (9.5 cm)
Package 1 Weight	25.00 lb(US) (11.34 kg)