

Product data sheet

Characteristics

HEPD80C

Surge protection device, HEPD, 80kA, 120/240V, 1 phase, 3 wire, SPD type 1, consumer pack



Main

Product	Surge protection device
Range	Square D
Device Short Name	HEPD

Complementary

Voltage Rating	120/240 V AC
MCOV	150 V
SCCR	25 kA
Surge Current	80 kA per phase
Voltage Protection Rating	600 V L-N 600 V L - G 1000 V L - L 900 V N - G

Nominal Discharge Current	10 kA
Rated Current	10 kA
Number of Phases	1 phase
Wiring Configuration	3-wire (isolated ground)
Connection	Wire AWG 14

Local Signalling	1 LED green normal operation
Product destination	Load center
Cable length	34 in (863.60 mm)
Type of Packing	Consumer packaging
Height	3.23 in (82.04 mm)

Width	3.72 in (94.49 mm)
Depth	2.10 in (53.34 mm)

Environment

Ambient Operating	-31...149 °F (-35...65 °C)
Enclosure Rating	NEMA 4X
Standards	CSA C22.2 CUL UL 1449:ed. 3: type I

Ordering and shipping details

Category	08461-SURGE PROTECTION RESI
Discount Schedule	DE1B
GTIN	785901112839
Returnability	Yes
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	8.20 in (20.828 cm)
Package 1 Width	6.30 in (16.002 cm)
Package 1 Length	4.00 in (10.16 cm)
Package 1 Weight	28.80 oz (816.466 g)

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	 REACH Declaration
EU RoHS Directive	Compliant with Exemptions
China RoHS Regulation	 China RoHS Declaration
RoHS exemption information	 Yes