



Quality Products. Service Excellence.

Rack Mount Metered PDU *1589-AM Series*

20A | Single-Phase 125V | Front or Rear Facing 5-15/20R Outlets

Features

- Designed for power distribution from the front or rear of the unit.
- Panel dimensions are 1.75" high (1U) and 19" rack width.
- Available with a rocker switch or red pilot light to indicate power on.
- The 20 amp. series uses heavy 12 gauge wire cord - 12/3 SJT for extreme temperature ranges and integral NEMA 5-20P straight blade or L5-20P locking type moulded plug.



Specifications

- Includes 20 Amp, 125 VAC circuit breaker to prevent accidental overload.
- Unit includes - easy to read 0.37" high, red LED ammeter (1.38" x 0.88" display).
- Digital ammeter accuracy +/- 0.1 Amps
- UL/cUL recognized Standard UL1363 file No. E166039 & CSA C22.2 No. 308-14
- Operating temperature is from -20 degrees C to +60 degrees C
- Finished in textured RAL9005 black powder paint finish.
- TAA-compliant for GSA Schedule purchases.
- RoHS and REACH compliant.
- Manufactured in North America.



Plug Types



5-20P Straight Blade

L5-20P Locking Type

Accessories

- Mounting Hardware
- Rail Depth Adapter Kit

On/Off Switch Part No.	Illuminated Light Only Part No.	Overall Dimensions			Number of Outlets	Number of Outlets	Outlet NEMA Type	Cord Length (ft)	Plug Blade Type	NEMA Plug Type	Rack Units
		Height	Width	Depth	On Front	On Rear					
1589H6C1BKRFAM	1589T6C1BKRFAM	1.72	19.00	2.66	6	0	5-20R	6	Locking	L5-20P	1U

On/Off Switch Part No.	Illuminated Light Only Part No.	Overall Dimensions			Number of Outlets		Outlet NEMA Type	Cord Length (ft)	Plug Blade Type	NEMA Plug Type	Rack Units
		Height	Width	Depth	On Front	On Rear					
1589H6F1BKRFAM	1589T6F1BKRFAM	1.72	19.00	2.66	6	0	5-20R	6	Straight	5-20P	1U
1589H6C1BKRRAM	1589T6C1BKRRAM	1.72	19.00	2.66	0	6	5-20R	6	Locking	L5-20P	1U
1589H6F1BKRRAM	1589T6F1BKRRAM	1.72	19.00	2.66	0	6	5-20R	6	Straight	5-20P	1U

Data subject to change without notice

© 2022. Hammond Manufacturing Ltd. All rights reserved.