

Product data sheet

Characteristics

NFRPL442L4TFL

Panelboard accessory, NF, deadfront service kit, 400A, 3 phase, 42 spaces, thru feed lugs



Main

Product	Cover plate
Accessory / separate part category	Replacement part
Provided equipment	Lug 4

Complementary

Number of spaces	42
Number of circuits	42
Device Application	Main lug
Current Rating	400 A
Number of Phases	3 phase
Tightening torque	45...50 Lbf.in (5.08...5.65 N.m) 0.02...0.10 in ² (13.30...67.43 mm ²) (AWG 6...AWG 2/0) 100 lbf.in (11.30 N.m) 0.02...0.10 in ² (13.30...67.43 mm ²) (AWG 6...AWG 2/0)

Ordering and shipping details

Category	08338-NF (& SHARED) RTI ACCESSORIES
Discount Schedule	PE1A
GTIN	3606486139202
Returnability	No
Country of origin	US

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	7.00 lb(US) (3.175 kg)

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Nickel compounds, which is known to the State of California to cause cancer, and Bisphenol A (BPA), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
RECh Regulation	RECh Declaration
RECh free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Contractual warranty

Warranty

18 months
