

# GS1AM2

Auxiliary contacts, TeSys GS, 2 C/O, early break, front mounting, for GS1 50 to 400A with direct right handle



## Main

Range of Product	TeSys
Device short name	GS1AM
Product or Component Type	Auxiliary contact
Contact application	O and I position signalling
Range compatibility	TeSys TeSys GS GS1 F fuse-switch disconnecter TeSys TeSys GS GS1G fuse-switch disconnecter TeSys TeSys GS GS1 J fuse-switch disconnecter TeSys TeSys GS GS1 K fuse-switch disconnecter TeSys TeSys GS GS1 L fuse-switch disconnecter TeSys TeSys GS GS1 N fuse-switch disconnecter TeSys TeSys GS GS1Q fuse-switch disconnecter
Contacts type and composition	2 C/O
Contact operation	Early-break
[I <sub>th</sub> ] conventional free air thermal current	16 A (at 104 °F (40 °C))
[I <sub>e</sub> ] rated operational current	5 A 127 V AC-15 4 A 230 V AC-15 3 A 400/415 V AC-15 2 A 440 V AC-15 12 A 24 V DC-13 2 A 48 V DC-13 0.6 A 110 V DC-13 0.4 A 220 V DC-13

## Complementary

Mechanical durability	1 Mcycles
Electrical durability	30000 cycles AC-15
Switch rated current	50 A 63 A 100 A 125 A 160 A 200 A 250 A 315 A 400 A
Fuse type	NFC DIN BS
Type of operating handle	Direct right side
Mounting Location	Front face
Net Weight	0.08 lb(US) (0.035 kg)

## Ordering and shipping details

Category	18402-WORLD SERVICE PARTS(CONTROL ACCESS)
Discount Schedule	CP10
GTIN	3389110563221
Returnability	No
Country of origin	FR

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	1.18 in (3.0 cm)
Package 1 Width	2.76 in (7.0 cm)
Package 1 Length	3.94 in (10.0 cm)
Package 1 Weight	1.23 oz (35.0 g)
Unit Type of Package 2	S01
Number of Units in Package 2	20
Package 2 Height	5.91 in (15.0 cm)
Package 2 Width	5.91 in (15.0 cm)
Package 2 Length	15.75 in (40.0 cm)
Package 2 Weight	2.28 lb(US) (1.036 kg)

## Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Styrene, which is known to the State of California to cause cancer. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
RoHS exemption information	<a href="#">Yes</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	<a href="#">End Of Life Information</a>

## Contractual warranty

Warranty	18 months
----------	-----------