
YGHHC34C26 Compression Grounding C-TAP Connector



By Burndy
Catalog # YGHHC34C26

Compression ground connector, Material: Copper, Range Run: 300 kcmil-500 kcmil or 3/4" Rod; Tap: 6 SOL-2/0 STR

Features

- Double Figure C Connector, C-Shaped opening permits two continuous parallel cables into conductor groove
- Qualified to IEEE-837 2014
- Prefilled with PENETROX compound and strip sealed

Application

Cable to Cable or Cable to Ground Rod Applications

Specifications

Standards - Industry Standards Met	• UL467 • IEEE 837 • IEEE 837 2014 Qualified • UL 486A-486B
Standards - RoHS Compliance Status	CM
Certification - UL Listed Direct Burial	Yes
Industry Standard(s)	• UL 467 • IEEE 837 • IEEE 837 2014 Qualified • UL 486A-486B
Certification - CSA Approved	[Delete]

Conductor

Conductor - Rod Run Range	3/4" Rod
Conductor - Copper Str Run Range	300 - 500 kcmil
Conductor - Copper Solid Tap Range	6 Solid - 2/0 Solid
Conductor - Copper Str Tap Range	6 Stranded - 2/0 Stranded

Configuration

Connector Type	Tap

Dimensions

Package Height	0.000 in
Dimension - Height mm	0 mm
Package Weight	0.000 lb.
Package Length	0.000 in
Package Width	0.000 in
Width	2.13 in

General

Plated	No
Product Family	Grounding and Bonding Connectors>"Hyground" Compression Grounding Connectors>C-Taps
Trade Name	HYTAP™
Die Index	1011
Product Type	Compression
UPC	621945456259
Type	Taps
Construction Material - Main	Copper
Material	Copper
UPC 12 Digit	621945456259
UPC 14 Digit GTIN	00621945456259

Logistics

Pallet Quantity	2400
Carton Quantity	20

Product Assets

Catalog [English]
Installation Manual [English]

© 2026 Hubbell Incorporated. All rights reserved