



## Main

Product	End tap box
Range	I-Line

## Complementary

Rated Current	1600 A aluminium
Rated Operational Voltage	600 V AC/DC 50/60 Hz
Length	29.14 in (740.16 mm)
Height	28 in (711.20 mm)
Width	14.88 in (377.95 mm)
Material	Aluminium: busbar
I-LINE Value End	Bolt
Number of Phases	3 phase
For Use with	Busbar trunking 1600 A aluminium
Protection Type	50 percent capacity integral ground bus
Wiring Configuration	4-wire

## Environment

Standards	UL 857 CSA C22.2 No 27:1994 IEC 61439-6
-----------	---

## Ordering and shipping details

Category	20010-1600A AL FEEDER BUS IP54 THERMAL
Discount Schedule	PE8
GTIN	785901815884
Returnability	Yes
Country of origin	US

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	29.13 in (74.0 cm)
Package 1 Width	14.88 in (37.8 cm)
Package 1 Length	27.99 in (71.1 cm)
Package 1 Weight	175.00 lb(US) (79.379 kg)

## Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Nickel compounds, which is known to the State of California to cause cancer, and Bisphenol A (BPA), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
RoHS exemption information	<a href="#">Yes</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	No need of specific recycling operations
PVC free	Yes

## Contractual warranty

Warranty	18 months
----------	-----------