



Main

Range	TeSys
Device short name	LUF
Product or Component Type	Function module
Product Compatibility	LUCB LUCM LUCD

Complementary

Mounting Mode	Plug-in
Mounting Location	Front side
Main function available	Indication of motor load
[Us] rated supply voltage	24 V DC
Analogue output current	4...20 mA
Type of output signal	Value of I average/I _r ratio within the range of 0 to 2 for LUCB and LUCD Value of I average/I _r ratio within the range of 0 to 3 for LUCM
Load impedance ohmic	100 Ohm typical <= 500 Ohm
Measurement accuracy	+/- 10 % with multifunction control unit 1 % of I _r +/- 6 % with advanced control unit
Connection pitch	0.15 in (3.81 mm)
Connections - terminals	Screw clamp terminals 1 0.00...0.00 in ² (0.14...1 mm ²) flexible without cable end Screw clamp terminals 1 0.00...0.00 in ² (0.14...1 mm ²) rigid without cable end Screw clamp terminals 1 0.00...0.00 in ² (0.25...0.5 mm ²) flexible with cable end Screw clamp terminals 1 0.00...0.00 in ² (0.25...1 mm ²) flexible with cable end Screw clamp terminals 2 0.00...0.00 in ² (0.14...0.5 mm ²) rigid without cable end Screw clamp terminals 2 0.00...0.00 in ² (0.14...0.75 mm ²) flexible without cable end Screw clamp terminals 2 0.00...0.00 in ² (0.25...0.34 mm ²) flexible with cable end Screw clamp terminals 2 0.00 in ² (0.5 mm ²) flexible with cable end
Associated cable type	AWG 26...AWG 16
Tightening torque	1.77...2.21 lbf.in (0.2...0.25 N.m) 0.10 in (2.5 mm) flat
Net Weight	0.11 lb(US) (0.05 kg)

Ordering and shipping details

Category	22399-TESYS U, ACCESSORIES
Discount Schedule	I11
GTIN	3389110365498
Returnability	Yes
Country of origin	FR

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3.74 in (9.500 cm)
Package 1 Width	1.30 in (3.300 cm)
Package 1 Length	1.85 in (4.700 cm)
Package 1 Weight	1.76 oz (50.000 g)
Unit Type of Package 2	S01
Number of Units in Package 2	36
Package 2 Height	5.91 in (15.000 cm)
Package 2 Width	5.91 in (15.000 cm)
Package 2 Length	15.75 in (40.000 cm)
Package 2 Weight	4.49 lb(US) (2.035 kg)

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Contractual warranty

Warranty	18 months
----------	-----------