

# Product data sheet

Specifications



Complete illuminated push button,  
Harmony XB6, green square flush,  
16mm, latching, 1NO, 12...24V

XB6CF3B1B

Product availability: Stock - Normally stocked in distribution facility

## Main

|                               |                                  |
|-------------------------------|----------------------------------|
| Range of Product              | Harmony XB6                      |
| Product or Component Type     | Complete illuminated push-button |
| Device short name             | XB6                              |
| Bezel material                | Plastic                          |
| Mounting diameter             | 0.6 in (16 mm)                   |
| Sale per indivisible quantity | 1                                |
| Shape of signaling unit head  | Square                           |
| Type of operator              | latching                         |
| Operator profile              | Green flush, unmarked            |
| Contacts type and composition | 1 NO                             |
| Contact operation             | Slow-break                       |
| Connections - terminals       | Faston connectors 2.8 x 0.5 mm   |
| Light source                  | LED                              |
| Bulb base                     | Integral LED                     |
| [Us] rated supply voltage     | 12...24 V AC/DC                  |

## Complementary

|                                        |                                                                               |
|----------------------------------------|-------------------------------------------------------------------------------|
| Height                                 | 0.7 in (18 mm)                                                                |
| Width                                  | 0.7 in (18 mm)                                                                |
| Depth                                  | 2.2 in (57 mm)                                                                |
| Terminals description ISO n°1          | (13-14)NO                                                                     |
| Product Weight                         | 0.049 lb(US) (0.022 kg)                                                       |
| Operating position                     | Any position                                                                  |
| Positive opening                       | With EN/IEC 60947-5-1 appendix K                                              |
| Operating travel                       | 0.04 in (1 mm) NO changing electrical state)<br>0.1 in (3.5 mm) total travel) |
| Operating force                        | 3.5 N NO changing electrical state                                            |
| Contacts material                      | Silver alloy (Ag/Ni)                                                          |
| Short-circuit protection               | 6 A cartridge fuse gG                                                         |
| [UI] rated insulation voltage          | 250 V 3)EN/IEC 60947-1                                                        |
| [Uimp] rated impulse withstand voltage | 4 kV EN/IEC 60947-1                                                           |

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

|                                |                                                                                                                                                                                 |
|--------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| [Ie] rated operational current | 3 A 120 V, AC-15, B300 EN/IEC 60947-5-1<br>1.5 A 240 V, AC-15, B300 EN/IEC 60947-5-1<br>0.1 A 250 V, DC-13, R300 EN/IEC 60947-5-1<br>0.22 A 125 V, DC-13, R300 EN/IEC 60947-5-1 |
| Electrical durability          | 1000000 cycles, AC-15 230 V 3600 cyc/h 0.5 EN/IEC 60947-5-1 appendix C<br>1000000 cycles, DC-13 230 V 3600 cyc/h 0.5 EN/IEC 60947-5-1 appendix C                                |
| Electrical reliability         | $\Lambda = 10\exp(-8)$ 5 V 1 mA with confidence level of 90 % IEC 60947-5-4                                                                                                     |
| Signalling type                | Steady                                                                                                                                                                          |
| Supply voltage limits          | 6...30 V AC/DC                                                                                                                                                                  |
| Current Consumption            | 15 mA                                                                                                                                                                           |
| Surge withstand                | 1 kV direct contact IEC 61000-4-5<br>2 kV in free air IEC 61000-4-5                                                                                                             |

## Environment

|                                       |                                                                                                                                |
|---------------------------------------|--------------------------------------------------------------------------------------------------------------------------------|
| Protective treatment                  | TC                                                                                                                             |
| Ambient Air Temperature for Storage   | -40...158 °F (-40...70 °C)                                                                                                     |
| Ambient Air Temperature for Operation | -13...158 °F (-25...70 °C)                                                                                                     |
| Electrical shock protection class     | Class II conforming to IEC 61140                                                                                               |
| IP degree of protection               | IP65 IEC 60529                                                                                                                 |
| NEMA degree of protection             | NEMA 13 UL 50<br>NEMA 4 UL 50<br>NEMA 4X UL 50<br>NEMA 13 CSA C22.2 No 94<br>NEMA 4 CSA C22.2 No 94<br>NEMA 4X CSA C22.2 No 94 |
| Standards                             | JIS C 852<br>EN/IEC 60947-1<br>CSA C22.2 No 14<br>UL 508<br>EN/IEC 60947-5-5<br>EN/IEC 60947-5-1<br>JIS C 4520                 |
| Product Certifications                | CSA<br>GOST<br>UL<br>CCC                                                                                                       |
| Vibration resistance                  | +/- 3 mm (f= 2...500 Hz) conforming to IEC 60068-2-6<br>5 gn (f= 2...500 Hz) conforming to IEC 60068-2-6                       |
| Shock resistance                      | 30 gn 18 ms) half sine wave acceleration IEC 60068-2-27<br>50 gn 11 ms) half sine wave acceleration IEC 60068-2-27             |
| Resistance to fast transients         | 2 kV IEC 61000-4-4                                                                                                             |
| Resistance to electromagnetic fields  | 9.1 V/m (10 V/m) IEC 61000-4-3                                                                                                 |
| Resistance to electrostatic discharge | 6 kV on contact (on metal parts) IEC 61000-4-2<br>8 kV in free air (in insulating parts) IEC 61000-4-2                         |
| Electromagnetic emission              | Class B IEC 55011                                                                                                              |

## Ordering and shipping details

|                   |               |
|-------------------|---------------|
| Category          | US10CS222459  |
| Discount Schedule | 0CS2          |
| GTIN              | 3389110763935 |
| Returnability     | Yes           |
| Country of origin | FR            |

## Packing Units

|                              |                         |
|------------------------------|-------------------------|
| Unit Type of Package 1       | PCE                     |
| Nbr. of units in pkg.        | 1                       |
| Package 1 Height             | 1.772 in (4.500 cm)     |
| Package 1 Width              | 2.165 in (5.500 cm)     |
| Package 1 Length             | 2.362 in (6.000 cm)     |
| Package weight(Lbs)          | 0.741 oz (21.000 g)     |
| Unit Type of Package 2       | S02                     |
| Number of Units in Package 2 | 75                      |
| Package 2 Height             | 5.906 in (15.000 cm)    |
| Package 2 Width              | 11.811 in (30.000 cm)   |
| Package 2 Length             | 15.748 in (40.000 cm)   |
| Package 2 Weight             | 4.182 lb(US) (1.897 kg) |

## Contractual warranty

|                      |    |
|----------------------|----|
| Warranty (in months) | 18 |
|----------------------|----|



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

### Use Better

| Materials and Substances               |                                                                                                                                                                                                                                                                                             |
|----------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Packaging made with recycled cardboard | Yes                                                                                                                                                                                                                                                                                         |
| Packaging without single use plastic   | No                                                                                                                                                                                                                                                                                          |
| SCIP Number                            | 902182a2-9610-45f2-840e-6da530122efe                                                                                                                                                                                                                                                        |
| EU RoHS Directive                      | <a href="#">Compliant By Exemption</a>                                                                                                                                                                                                                                                      |
| REACH Regulation                       | <a href="#">Reference contains Substances of Very High Concern above the threshold</a>                                                                                                                                                                                                      |
| California proposition 65              | WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a> |

### Use Longer

| Lifetime extension |    |
|--------------------|----|
| Repair             | No |


### Use Again

| Repack and remanufacture |                                                                                                                              |
|--------------------------|------------------------------------------------------------------------------------------------------------------------------|
| Take-back                | No                                                                                                                           |
| WEEE Label               | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins. |

Dimensions Drawings

Square Head Pushbutton

Dimensions




e panel thickness 1 to 6 mm/0.03 to 0.23 in.

Mounting and Clearance

Panel Cut-out

For Square or Circular Head



Technical Illustration

Dimensions

