

TYPE Q-M**FINGRIP™ Terminal**

Uninsulated Male

Quick Disconnect Terminal



Chamfered barrel opening assures quick and easy wire insertion. Dimpled female socket and male tab detent ensure firm grip.

Catalog Number	Wire Range	NEMA Tab Size	Hand Tool	Wire Strip Length
Q18M18X02D	22 - 8	.187 × .020	MR20, Y10D	7/32"
Q18M25X03D		.250 × .032		
Q14M18X02D	16 - 14	.187 × .020		
Q14M25X03D		.250 × .032		

TYPE QP-M**FINGRIP™ Terminal**

Vinyl Insulated Male

Quick Disconnect Terminal



Easy entry shroud has smooth funnel which assures no hang up wire insertion. Color coded for quick and easy identification. Two piece construction.

Catalog Number	Wire Range	NEMA Tab Size	Hand Tool	Sleeve Color	Wire Strip Length
QP18M18X02D	22 - 18	.187 × .020	Y10D	Red	5/16"
QP18M25X03D		.250 × .032			
QP14M18X02D	16 - 14	.187 × .020			
QP14M25X03D		.250 × .032		Blue	

TYPE QN-M**FINGRIP™ Terminal**

Nylon Insulated Male

Quick Disconnect Terminal



Smooth copper funnel wire entry greatly reduces the possibility of wire stubbing and provides maximum wire support.

Catalog Number	Wire Range	NEMA Tab Size	Hand Tool	Sleeve Color	Wire Strip Length
QN18M18X02D	22 - 18	.187 × .020	Y10D	Red	9/32"
QN18M25X03D		.250 × .032			
QN14M18X02D	16 - 14	.187 × .020			
QN14M2503D		.250 × .032		Blue	

TYPES YSV, YSV-L**HYLINK™ Splices**

600 Volt Maximum



HYLINK™ Type YSV seamless splice connector is used to splice stranded and solid copper conductors in virtually all heavy duty industrial and general purpose applications.

Catalog Number	Wire Range Code AWG Str. and Sol. Aircraft-AN	Bulk Catalog Number	Installation Tooling HYTOOL™
YSV18BOX	22 - 18 str. & sol.	YSV18	Non-Ratchet: Y10D, Y10-22
YSV14BOX	20 - 14 str. 20 - 12 sol.	YSV14	Ratchet: MR20, Y8MRB-1, MR8-9Q*
YSV10BOX	12 - 10 str. & sol.	YSV10	
YSV9C-LBOX	9 str.	YSV9C-L	Non-Ratchet: MY28, MY29-3, MY29-11
YSV8C-LBOX	8 str.	YSV8C-L	Ratchet: Y8MRB-1†, MR8-9Q*, Y1MRTC ▲

*Remove stop plate.

† Use #10 groove.

▲ For 8 str. only.

TYPES SP, BS**VINYLINK™ Splice**

600 Volts



The Type SP VINYLINK™ is a PVC insulated seamless butt splice. Type SP VINYLINK™ is designed to accommodate a broad range of 600 volt cables.

Catalog Number	Wire Range	Color Code	Bulk Catalog Number	Installation Tooling
SP16	22 - 16	Red	BS16	Non-Ratchet: Y10-22, Y10D
SP14	16 - 14	Blue	BS14	Ratchet:
SP10	12 - 10	Yellow	BS10	MR8-89-1, MR15, MR8G-98

TYPES SN, YSE-HN**INSULINK™ Splice**

600 Volt, 105° C



The Type SN INSULINK™ is a high quality nylon-insulated butt splice designed to meet heavy duty application requirements. Meets the functional requirements of MIL-T-7928 (ASG) and conforms to the requirements of NAS1388.

Catalog Number	Wire Range	Color Code	Bulk Catalog Number	Installation Tooling
SN18	22-18	Red	YSE18HN	Non-Ratchet: Y10D
SN14	16-14	Blue	YSE14HN	Ratchet:
SN10	12-10	Yellow	YSE10HN	MR8-85, MR18