



CFL

CFL lamps provide the same amount of light (lumens) as regular incandescent lamps, but have a lower wattage rating. As a result, they consume less energy and cause less pollution. ALL STANDARD CFL lamps meet NEMA voluntary commitment on mercury content in CFL lamps and are all cULus listed, where applicable.

Specialty



20 W; MOL: 5 1/8 in. (130 mm)
Ø 2 9/32 in. (68 mm)

**High Power
Factor**



MOL: 5 1/16 in. (154 mm)
Ø 2 1/4 in. (57 mm)

Trilight

| Order code | Description | Watts (W) | Base | Color temp. (K) | Lumen output (lm) | Average life (hrs) | CRI | Incandescent equivalent (W) | Case qty (inner/master) |
|--------------------------|-------------------------------|----------------|------|-----------------|-----------------------|--------------------|-----|-----------------------------|-------------------------|
| High Power Factor | | | | | | | | | |
| 58404 | CF20/HPF/27K/SPIRAL/E26/STD | 20 | E26 | 2 700 | 1 200 | 10 000 | 82 | 75 | 12/48 |
| Trilight | | | | | | | | | |
| 58959 | CF13/20/25/27K/SPIRAL/E26/STD | 13 20 25 | E26 | 2 700 | 900 1 200 1 550 | 8 000 | 80 | 60 75 100 | 6/48 |

T2 Spiral



MOL: 4 11/32 in. (110 mm)
Ø 2 5/32 in. (65 mm)

18 W



MOL: 5 1/16 in. (129 mm)
Ø 2 1/8 in. (54 mm)

26 W

| Order code | Description | Watts (W) | Base | Color temp. (K) | Lumen output (lm) | Average life (hrs) | CRI | Incandescent equivalent (W) | Case qty (inner/master) |
|--------------------|----------------------------|-----------|------|-----------------|-------------------|--------------------|-----|-----------------------------|-------------------------|
| 18 watts | | | | | | | | | |
| 62832 ¹ | CF18/T2/27K/SPIRAL/E26/STD | 18 | E26 | 2 700 | 1 250 | 12 000 | 82 | 75 | 6/48 |
| 62833 ¹ | CF18/T2/30K/SPIRAL/E26/STD | 18 | E26 | 3 000 | 1 250 | 12 000 | 82 | 75 | 6/48 |
| 62834 ¹ | CF18/T2/35K/SPIRAL/E26/STD | 18 | E26 | 3 500 | 1 250 | 12 000 | 82 | 75 | 6/48 |
| 26 watts | | | | | | | | | |
| 63388 ¹ | CF26/T2/27K/SPIRAL/E26/STD | 26 | E26 | 2 700 | 1 750 | 10 000 | 82 | 100 | 6/48 |
| 63389 ¹ | CF26/T2/30K/SPIRAL/E26/STD | 26 | E26 | 3 000 | 1 750 | 10 000 | 82 | 100 | 6/48 |
| 63391 ¹ | CF26/T2/41K/SPIRAL/E26/STD | 26 | E26 | 4 100 | 1 750 | 10 000 | 82 | 100 | 6/48 |
| 63392 ¹ | CF26/T2/50K/SPIRAL/E26/STD | 26 | E26 | 5 000 | 1 750 | 10 000 | 82 | 100 | 6/48 |

GU24 Based



13 W: MOL: 3 5/8 in. (92 mm)
Ø 1 13/16 in. (46 mm)
18 W: MOL: 4 13/32 in. (112 mm)
Ø 1 1/8 in. (54 mm)
23 W: MOL: 4 13/32 in. (112 mm)
Ø 1 1/8 in. (54 mm)

Spiral (GU24)



23 W: MOL: 4 27/32 in. (123 mm)
Ø 2 1/8 in. (54 mm)

Dimmable Spiral (GU24)

| Order code | Description | Watts (W) | Base | Color temp. (K) | Lumen output (lm) | Average life (hrs) | CRI | Incandescent equivalent (W) | Case qty (inner/master) |
|--------------------------|-----------------------------|-----------|------|-----------------|-------------------|--------------------|-----|-----------------------------|-------------------------|
| Spiral | | | | | | | | | |
| 61843 | CF13/T2/35K/SPIRAL/GU24/STD | 13 | GU24 | 3 500 | 880 | 10 000 | 82 | 60 | 6/48 |
| 61845 | CF18/T2/27K/SPIRAL/GU24/STD | 18 | GU24 | 2 700 | 1 150 | 10 000 | 82 | 75 | 6/48 |
| 61846 | CF23/T2/27K/SPIRAL/GU24/STD | 23 | GU24 | 2 700 | 1 600 | 10 000 | 82 | 100 | 6/48 |
| 61847 | CF23/T2/41K/SPIRAL/GU24/STD | 23 | GU24 | 4 100 | 1 600 | 10 000 | 82 | 100 | 6/48 |
| Spiral - Dimmable | | | | | | | | | |
| 60921 ² | CF23/D/27K/SPIRAL/GU24/STD | 23 | GU24 | 2 700 | 1 500 | 10 000 | 82 | 100 | 6/48 |



High Wattage Spiral



| Order code | Description | Watts (W) | Base | Color temp. (K) | Lumen output (lm) | Average life (hrs) | CRI | Incandescent equivalent (W) | Case qty (inner/master) |
|------------------|---------------------------|-----------|------|-----------------|-------------------|--------------------|-----|-----------------------------|-------------------------|
| 32 watts | | | | | | | | | |
| 60932 | CF32/27K/SPIRAL/E26/STD | 32 | E26 | 2 700 | 2 000 | 10 000 | 82 | 120 | 6/48 |
| 60936 | CF32/50K/SPIRAL/E26/STD | 32 | E26 | 5 000 | 2 000 | 10 000 | 82 | 120 | 6/48 |
| 58412 | CF32/65K/SPIRAL/E26/STD | 32 | E26 | 6 500 | 2 100 | 10 000 | 82 | 120 | 6/48 |
| 40 watts | | | | | | | | | |
| 60940 | CF40/35K/SPIRAL/E26/STD | 40 | E26 | 3 500 | 2 600 | 10 000 | 82 | 150 | 6/48 |
| 60942 | CF40/50K/SPIRAL/E26/STD | 40 | E26 | 5 000 | 2 600 | 10 000 | 82 | 150 | 6/48 |
| 60943 | CF40/65K/SPIRAL/E26/STD | 40 | E26 | 6 500 | 2 600 | 10 000 | 82 | 150 | 6/48 |
| 55 watts | | | | | | | | | |
| 60922 | CFL55/27K/SPIRAL/E26/STD | 55 | E26 | 2 700 | 3 700 | 10 000 | 82 | 300 | 6/48 |
| 60923 | CFL55/50K/SPIRAL/E26/STD | 55 | E26 | 5 000 | 3 700 | 10 000 | 82 | 300 | 6/48 |
| 65 watts | | | | | | | | | |
| 60924 | CFL65/27K/SPIRAL/E26/STD | 65 | E26 | 2 700 | 4 300 | 10 000 | 82 | 300 | 6/48 |
| 60925 | CFL65/50K/SPIRAL/E26/STD | 65 | E26 | 5 000 | 4 300 | 10 000 | 82 | 300 | 6/48 |
| 85 watts | | | | | | | | | |
| 60926 | CFL85/27K/SPIRAL/E26/STD | 85 | E26 | 2 700 | 5 400 | 10 000 | 82 | 350 | 6/12 |
| 60927 | CFL85/50K/SPIRAL/E26/STD | 85 | E26 | 5 000 | 5 400 | 10 000 | 82 | 350 | 6/12 |
| 105 watts | | | | | | | | | |
| 60929 | CFL105/50K/SPIRAL/E39/STD | 105 | E39 | 5 000 | 6 500 | 10 000 | 82 | 400 | 6/12 |

