



Main

Range of Product	Magelis XBTGH
Product or Component Type	Junction box
Product Specific Application	For XBTGH advanced hand-held panel

Complementary

[Us] rated supply voltage	24 V DC
Supply voltage limits	19.2...28.8 V
Inrush current	30 A
Power Consumption in W	6.3 W
Electrical connection	1 connector 24-pin connector hand-held panel 1 connector RJ45 Ethernet TCP/IP 1 male connector SUB-D 9 RS232C/RS422/RS485 <= 115.2 kbits/s COM1 serial link Screw terminal block 24 inputs/outputs
Port Ethernet	10BASE-T/100BASE-TX
Enclosure Material	PPT
Fixing mode	By 4 M4 screws 1.5 to 10 mm thick panel Clip-on 35 mm symmetrical DIN rail
Marking	CE

Environment

Immunity to microbreaks	10 ms
Standards	FCC Class A EN 61131-2 IEC 61000-6-2 UL 508
Product Certifications	cULus[RETURN]C-tick
Ambient Air Temperature for Operation	32...122 °F (0...50 °C)
Ambient Air Temperature for Storage	-4...140 °F (-20...60 °C)
Operating altitude	<= 6561.68 ft (2000 m)
IP degree of protection	IP20 rear panel) IP65 front panel)
Shock resistance	15 gn 11 ms IEC 60068-2-27
Vibration resistance	1 gn 9...150 Hz) 3.5 mm 5...9 Hz)
Relative Humidity	0...90 % without condensation or dripping water
Resistance to electrostatic discharge	6 kV IEC 61000-4-2 level 3
Resistance to electromagnetic fields	9.14 V/m (10 V/m) IEC 61000-4-3
Resistance to fast transients	2 kV IEC 61000-4-4 level 3

Ordering and shipping details

Category	22569-MAGELIS XBT-GT (AND XBT-G)
Discount Schedule	MC2
GTIN	3595864003191
Returnability	No
Country of origin	JP

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	6.69 in (17.000 cm)
Package 1 Width	8.86 in (22.500 cm)
Package 1 Length	10.63 in (27.000 cm)
Package 1 Weight	2.61 lb(US) (1.184 kg)
Unit Type of Package 2	S03
Number of Units in Package 2	2
Package 2 Height	11.81 in (30.000 cm)
Package 2 Width	11.81 in (30.000 cm)
Package 2 Length	15.75 in (40.000 cm)
Package 2 Weight	6.39 lb(US) (2.900 kg)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Contractual warranty

Warranty	18 months
----------	-----------