



Representative

Catalog Number: RGC272BLD-C
Product ID: 7TBA133580R1419
UPC Number: 62461635981
Status: A

Battery Unit, Battery Type: lead-calcium, Voltage DC: 6V, Battery Wattage: 27W, self-powered, Colour: factory white, 120VAC, two lamps, Lamp Type: MR16 LED, Lamp Voltage: 6V, Lamp Wattage: 4W, line cord, Head Style: standard, Battery Run Time (Minimum): 30 minutes, counter

Fully-automatic labour-saving commercial emergency lighting unit.

- Quick and easy installation, pre-assembled cordset, no batteries or board to remove before installation
- Universal Spider knockout pattern for junction box mounting
- Fully automatic solid-state charger with test switch and AC-on pilot light
- Sealed dust-proof transfer relay circuit and low-voltage disconnect
- Heads require no tools for orientation

North American Specifications (UNSPSC)

UNSPSC	39111709 Emergency light unit
IGCC	3940 Emergency light unit
Type	Battery Unit
Application	Institutional, Commercial, Hospitality
Standard	CSA
Wattage	27 W
Voltage Rating	120 VAC ; 6 VDC
Battery	Lead-calcium
Battery Runtime	30 minutes
Lamp Type	MR16 LED
Number Of Lamps	2
Size	9-1/8 Inches Height x 12-3/4 Inches Width
Material	Cabinet: Steel
Mounting	Wall
Color	Factory white
Lamp Wattage	4 W

European Specifications (ETIM)

ETIM	EC001957 Emergency luminaire
Lamp type	LED exchangeable
With lamp	Y
Lamp power	4W
Material housing	Steel
Colour housing	White
Battery quality	Lead
Voltage type	AC/DC
Nominal voltage	120-120V
Width	323mm
Height/depth	231mm

Packaging

Inner Quantity	1
Inner Dimensions (inches)	1x1x.1
Outer Quantity	4
Outer Dimensions (inches)	1x1x1
Weight Uom	7 lbs. Each



Documents / Support Tools

Catalog Page	Available on Website
Instruction Sheet	Available on Website

For further technical assistance, please contact us...

ABB Installation Products Canada
700, Thomas Avenue
Saint-Jean-sur-Richelieu, QC
J2X 2M9
www.tnb.ca

ABB Installation Products Technical Support
<http://www.tnb.ca/en/contactus/?id=ALL>

Hours: 7h00 - 18h00
Monday-Friday