



Main

Range	ClimaSys
Product name	ClimaSys CC
Product or Component Type	Thermostat
Temperature setting range	41...140 °F (5...60 °C)
Information Displayed	Temperature in °C

Complementary

Input voltage	250 V
Sensor Type	Bimetal
Contacts type and composition	1 NO/NC
Contact resistance	10 mOhm
Service Life in Cycles	100000 cycles
Maximum switching capacity	4 A 250 V AC inductive 0.6 30 W DC 10 A 250 V AC inductive
Electrical connection	4 terminals 2.5 mm ²
Mounting Mode	Clipped
Height	External 2.68 in (68 mm)
Width	External 2.20 in (56 mm)
Depth	External 1.73 in (44 mm)
Net Weight	3.53 oz (100 g)
Mounting Location	Cross rails On mounting plate 35 mm DIN rail Spacial upright
Ambient Air Temperature for Operation	-4...176 °F (-20...80 °C)
IP Degree of Protection	IP20
Hysteresis	7 K +/- 0.4K
Number of outputs	1 heating function 1 ventilation function
Material	PC
Color	Light gray
Flame retardance	Self-extinguishing conforming to UL94 (material V0)
Product Certifications	UL

Ordering and shipping details

Category	80036-ENCLOSURE SYSTEMS ACCESSORIES
Discount Schedule	ES1
GTIN	3606480152559
Returnability	No
Country of origin	ES

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	1.97 in (5 cm)
Package 1 Width	2.17 in (5.5 cm)
Package 1 Length	2.76 in (7 cm)
Package 1 Weight	2.82 oz (80 g)
Unit Type of Package 2	CAR
Number of Units in Package 2	75
Package 2 Height	10.24 in (26 cm)
Package 2 Width	16.34 in (41.5 cm)
Package 2 Length	12.80 in (32.5 cm)
Package 2 Weight	16.38 lb(US) (7.428 kg)
Unit Type of Package 3	P12
Number of Units in Package 3	3000
Package 3 Height	77.95 in (198 cm)
Package 3 Width	31.50 in (80 cm)
Package 3 Length	47.24 in (120 cm)
Package 3 Weight	685.64 lb(US) (311 kg)

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations

Contractual warranty

Warranty	18 months
----------	-----------