



Main

Product or component type	Communication card
Range compatibility	Altivar 61 Altivar 71Q Altivar 71 Altivar 61Q
Communication port protocol	CC-Link
Connector type	Removable screw connector, 5 contacts at intervals of 3.81
Transmission rate	5 Mbps 10 Mbps 2.5 Mbps 156 kbps 625 kbps
Physical interface	2-wire RS 485

Complementary

Number of addresses	1...64
Communication service	Communication monitoring I/O data CC-Link drive profile
Display type	1 LED L.ERR (Error) 1 LED L.RUN (Running) 1 LED power 1 LED RD (Receive Data) 1 LED SD (Send Data) Graphic display terminal drive address Graphic display terminal transmission speed used
Net weight	0.66 lb(US) (0.3 kg)

Packing Units

Package 1 Weight	0.61 lb(US) (0.278 kg)
Package 1 Height	0.750 dm
Package 1 width	2.300 dm
Package 1 Length	1.650 dm

Offer Sustainability

REACH Regulation	REACH Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration
PVC free	Yes

Contractual warranty

Warranty	18 months
----------	-----------