



Main

Product or component type	Single Throw Safety Switch
Disconnecter device type	Fusible disconnect
Number of poles	3
Electrical connection	Lugs
Series name	Heavy duty

Complementary

Line Rated Current	60 A
Device composition	None
Device mounting	Surface
[Ue] rated operational voltage	600 V AC/DC
AWG gauge	AWG 14...AWG 3 copper or aluminium
Maximum Horse Power Rating	15 Hp 480 V AC 50...60 Hz 3 phase NEC 240.6 30 Hp 480 V AC 50...60 Hz 3 phase NEC 430.52 15 Hp 600 V AC 50...60 Hz 3 phase NEC 240.6 50 Hp 600 V AC 50...60 Hz 3 phase NEC 430.52 10 Hp 250 V DC 30 hp 600 V DC
Height	17.5 in (444.50 mm)
Maximum Width	10.5 in (266.70 mm)
Depth	6.38 in (162.05 mm)
Tightening torque	50 Lbf.In (5.65 N.m) AWG 3) 5.08 N.M (AWG 6...AWG 4) 4.52 N.M (AWG 8) 50 Lbf.In (5.65 N.m) 0.00...0.01 in ² (2.06...5.261 mm ²) AWG 14...AWG 10) 50 lbf.in (5.65 N.m) AWG 14...AWG 10)

Environment

Product certifications	CSA
NEMA degree of protection	NEMA 1 galvanized steel

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.