


TYPE ILSCONS

Features

- Color coded
- Funnel Entry
- Manufactured from high strength copper alloy
- Electro-tin plated
- Vinyl insulation
- Packaged in convenient small quantities
- UL Listed and CSA Certified for 600 volts, 90° C

Benefits

- Provides easy wire range identification
#22-16 AWG Red
#16-14 AWG Blue
#12-10 AWG Yellow
- Provides maximum conductivity
- Provides low contact resistance
- Provides tough pliable insulative qualities to protect connectors and wire from corrosion as well as providing some strain relief
- Attractive resealable packaging designed for merchandise racks
- Ensures reliability for copper conductor



| Catalog Number | Wire Range | Stud Size | Dimensions | | Maximum Wire Insulated Diameter | Connector Type |
|----------------|------------|-----------|------------|------|---------------------------------|--|
| | | | L | W | | |
| 44501-B100 | 16-22 | 6 | .835 | .252 | .145 | Vinyl Insulated Spade Terminals (Expanded) |
| 44501-B1000 | 16-22 | 6 | .835 | .252 | .145 | Vinyl Insulated Spade Terminals (Expanded) |
| 44503-B100 | 16-22 | 10 | .835 | .335 | .145 | Vinyl Insulated Spade Terminals (Expanded) |
| 44503-B1000 | 16-22 | 10 | .835 | .335 | .145 | Vinyl Insulated Spade Terminals (Expanded) |
| 44511-B100 | 14-16 | 6 | .827 | .236 | .175 | Vinyl Insulated Spade Terminals (Expanded) |
| 44511-B1000 | 14-16 | 6 | .827 | .236 | .175 | Vinyl Insulated Spade Terminals (Expanded) |
| 44513-B100 | 14-16 | 10 | .827 | .319 | .175 | Vinyl Insulated Spade Terminals (Expanded) |
| 44513-B1000 | 14-16 | 10 | .827 | .319 | .175 | Vinyl Insulated Spade Terminals (Expanded) |
| 44522-B50 | 10-12 | 10 | 1.004 | .354 | .255 | Vinyl Insulated Spade Terminals (Expanded) |
| 44522-B500 | 10-12 | 10 | 1.004 | .354 | .255 | Vinyl Insulated Spade Terminals (Expanded) |

Can be supplied in bulk. Consult factory for part number.

Other sizes available on request. Contact factory for pricing.

