



## Main

Product or component type	Plug-in unit
Range of product	I-Line
Circuit breaker type	M-frame
Trip unit technology	Electronic, basic, ET 1.0, LI

## Complementary

Protection type	Circuit breaker
Mounting mode	Bolt-on
[Ue] rated operational voltage	600 V AC
[In] rated current	400 A
Number of Phases	3 phases
Poles description	3P
Interrupt Rating	100 kA 240 V AC 65 kA 480 V AC 25 kA 600 V AC
[Ics] rated service short-circuit breaking capacity	80 %
Wiring configuration	4-wire (integral ground bus)
AWG gauge	AWG 3/0...500 kcmil 3 phase and neutral AWG 6...300 kcmil 4 ground
Depth	20.24 in (514 mm)
Height	46.22 in (1174 mm)
Width	22.99 in (584 mm)
Condition of use	Vertical installation

## Environment

Product certifications	UL listed file E22182
------------------------	-----------------------

---

Standards	UL 857
-----------	--------

---

## Packing Units

---

Package 1 Weight	284.00 lb(US) (128.820 kg)
------------------	----------------------------

---

## Offer Sustainability

---

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS declaration</a> Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	<a href="#">Product Environmental Profile</a>

---