

# CH325NAWK

Safety switch, heavy duty, fusible, 400A, 240 VAC/250VDC, 3 poles, 125hp, NEMA 12, neutral



## Main

Product	Single Throw Safety Switch
Disconnect Type	Fusible disconnect
Number of Poles	3
Electrical Connection	Lugs
Duty Rating	Heavy duty

## Complementary

Line Rated Current	400 A
Factory Installed Neutral	Neutral (factory installed)
Mounting Type	Surface
Voltage Rating	240 V DC 250 V AC
Motor power hp	50 Hp at 240 V AC 50...60 kHz for 3 phase motors 125 Hp at 240 V AC 50...60 kHz for 3 phase motors 50 hp at 250 V DC
Wire Size	AWG 1/0...750 kcmil copper or aluminium
Tightening torque	550 lbf.in (62.14 N.m) (AWG 1/0...750 kcmil)
Height	46.25 in (1174.75 mm)
Width	26.25 in (666.75 mm)
Depth	10.13 in (257.30 mm)

## Environment

Certifications	CSA
Enclosure Rating	NEMA 3R/12 galvanized steel

## Ordering and shipping details

Category	00153-C,CH&CHU CANADA SW NON-NEG
Discount Schedule	DE1
GTIN	785901344742
Returnability	No
Country of origin	US

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	12.99 in (33.0 cm)
Package 1 Width	27.01 in (68.6 cm)
Package 1 Length	50.98 in (129.5 cm)
Package 1 Weight	159.00 lb(US) (72.121 kg)

## Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
RoHS exemption information	<a href="#">Yes</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	No need of specific recycling operations
PVC free	Yes
Halogen content performance	Halogen free plastic parts product