



Main

Product or component type	Plug-in unit
Range of product	I-Line
Circuit breaker type	H-frame
Trip unit technology	Electronic, ammeter, Micrologic 6.2 A, LSIG

Complementary

Protection type	Circuit breaker
Mounting mode	Plug-in
[Ue] rated operational voltage	600 V AC
[In] rated current	60 A
Number of Phases	3 phases
Poles description	3P
Interrupt Rating	125 kA 240 V AC 100 kA 480 V AC 50 kA 600 V AC
[Ics] rated service short-circuit breaking capacity	80 %
Wiring configuration	4-wire (integral ground bus)
AWG gauge	AWG 8...AWG 3/0 1 phase and neutral AWG 6...AWG 2/0 1 ground
Depth	9.13 in (232 mm)
Height	8.50 in (216 mm)
Width	21.69 in (551 mm)

Environment

Product certifications	CSA C22.2 No 27 UL listed file E22182
------------------------	--

Standards	UL 857
-----------	--------

Packing Units

Package 1 Weight	32.00 lb(US) (14.515 kg)
------------------	--------------------------

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile
