

CD324NRB

Safety switch, general duty, fusible, 200A,
120/240 VAC, 3 poles, 30 hp, solid neutral,
NEMA 3R with bolt on hub



Main

| | |
|---------------------------|----------------------------|
| Product or Component Type | Single Throw Safety Switch |
| Series name | General duty |

Complementary

| | |
|--------------------------------|---|
| Device Composition | Neutral (factory installed) |
| Disconnect device type | Fusible disconnect |
| Short-circuit current | 100 kA maximum cartridge |
| Device mounting | Surface |
| Number of poles | 3 |
| Electrical Connection | Lugs |
| [Ue] rated operational voltage | 120/240 V AC |
| Motor power hp | 7.5 Hp at 240 V AC 50-60 Hz for 1 phase motors 15 Hp at 240 V AC 50-60 Hz for 3 phase motors 15 Hp at 240 V AC 50-60 Hz for 1 phase motors 30 hp at 240 V AC 50-60 Hz for 3 phase motors |
| AWG gauge | AWG 6...250 kcmil copper or aluminium |
| Tightening torque | 275 lbf.in (31.07 N.m) (AWG 6...250 kcmil) |
| Height | 29.25 in (742.95 mm) |
| Width | 19 in (482.60 mm) |
| Depth | 8.5 in (215.90 mm) |

Environment

| | |
|---------------------------|--------------------------|
| Product Certifications | CSA |
| NEMA degree of protection | NEMA 3R galvanized steel |

Ordering and shipping details

| | |
|-------------------|---------------------------------|
| Category | 00154-CD&CDU CANADA SW NON-NEGO |
| Discount Schedule | DE1A |
| GTIN | 785901391579 |
| Returnability | Yes |
| Country of origin | US |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Packing Units

| | |
|------------------------------|--------------------------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 8.50 in (21.59 cm) |
| Package 1 Width | 19.30 in (49.022 cm) |
| Package 1 Length | 30.50 in (77.47 cm) |
| Package 1 Weight | 56.50 lb(US) (25.628 kg) |

Offer Sustainability

| | |
|----------------------------|---|
| Sustainable offer status | Green Premium product |
| California proposition 65 | WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov |
| REACH Regulation | REACH Declaration |
| REACH free of SVHC | Yes |
| EU RoHS Directive | Compliant EU RoHS Declaration |
| Toxic heavy metal free | Yes |
| Mercury free | Yes |
| China RoHS Regulation | China RoHS Declaration |
| RoHS exemption information | Yes |
| Environmental Disclosure | Product Environmental Profile |
| Circularity Profile | No need of specific recycling operations |
| PVC free | Yes |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|