



Main

| | |
|-------------------|-------------------------|
| Product | Surge protection device |
| Range | Surgelogic |
| Device Short Name | IMA |

Complementary

| | |
|---------------------------|--|
| Voltage Rating | 277Y/480 V AC |
| MCOV | 320 V |
| SCCR | 200 kA |
| Surge Current | 240 kA per phase |
| Nominal Discharge Current | 20 kA |
| Number of Phases | 3 phase |
| Wiring Configuration | 4-wire |
| Connection | Lugs AWG 12...AWG 2 aluminium/copper 35.40 lbf.in (4 N.m) |
| Provided Equipment | Alarm enable/disable switch Diagnostic display Backplane Cables |
| Height | 6.13 in (155.7 mm) |
| Width | 9.86 in (250.4 mm) |
| Depth | 3.65 in (92.7 mm) |

Environment

| | |
|------------------|---|
| Enclosure Rating | NEMA 2 |
| Standards | UL 1449:ed. 4 CSA C22.2 No 8:1986 UL 96A:ed. 12 UL 1283 IEC 61643-1 |

Ordering and shipping details

| | |
|-------------------|----------------------------|
| Category | 08468-SURGE PROTECTION OEM |
| Discount Schedule | DE1B |
| GTIN | 785901600831 |
| Returnability | Yes |
| Country of origin | US |

Packing Units

| | |
|------------------------------|------------------------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 7.00 in (17.78 cm) |
| Package 1 Width | 9.00 in (22.86 cm) |
| Package 1 Length | 12.00 in (30.48 cm) |
| Package 1 Weight | 8.60 lb(US) (3.901 kg) |

Offer Sustainability

| | |
|----------------------------|---|
| California proposition 65 | WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov |
| REACH Regulation | REACH Declaration |
| EU RoHS Directive | Compliant with Exemptions |
| China RoHS Regulation | China RoHS Declaration |
| RoHS exemption information | Yes |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|