

# CH364RBEI

## 200A 3P Type3R 600V Heavy Duty Fusible Safety Switch With Electrical Interlock



### Main

Product or component type	Single Throw Safety Switch
Disconnecter device type	Fusible disconnect
Number of poles	3
Electrical connection	Lugs
Series name	Heavy duty

### Complementary

Line Rated Current	200 A
Device composition	None
Device mounting	Surface
[Ue] rated operational voltage	600 V AC/DC
AWG gauge	AWG 6...250 kcmil copper or aluminium
Maximum Horse Power Rating	50 Hp 480 V AC 50...60 Hz 3 phase NEC 240.6 125 Hp 480 V AC 50...60 Hz 3 phase NEC 430.52 60 Hp 600 V AC 50...60 Hz 3 phase NEC 240.6 150 Hp 600 V AC 50...60 Hz 3 phase NEC 430.52 40 Hp 250 V DC 50 hp at 600 V DC
Height	29.25 in (742.95 mm)
Maximum Width	18.63 in (473.20 mm)
Depth	8.5 in (215.90 mm)
Tightening torque	275 lbf.in (31.07 N.m) 0.02...0.20 in <sup>2</sup> (13.30...127 mm <sup>2</sup> ) AWG 6...250 kcmil

### Environment

Product certifications	CSA
NEMA degree of protection	NEMA 3R galvanized steel

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.