

Product data sheet

Specifications



wireless and battery less handy box,
1 simple action and 1 double action
buttons

ZBRM22AB0

Product availability: Stock - Normally stocked in distribution facility

Main

Range of Product	Harmony XB5R
Product or Component Type	Wireless and batteryless transmitter
Device short name	XB5R
Contact operation	1 simple and double action UP/DOWN push-buttons
Bezel material	Plastic
Fixing collar material	Plastic
Mounting diameter	0.9 in (22 mm)

Complementary

Kit composition	1 transmitter 1 set of caps 1 handy box 2 push-button head 0.9 in (22 mm) 2 fixing collars
Shape of signaling unit head	Round
Type of operator	spring return push-button with transmitter
Operator profile	Flush
Operator additional information	Set of caps
Product Weight	0.4 lb(US) (0.2 kg)
Mechanical durability	400000 cycles
Operating travel	0.2 in (4.3 mm) total travel)
Operating force	25 N C/O changing electrical state
Shock resistance	25 gn 6 ms) 6000 shocks IEC 60068-2-27 30 gn 18 ms) half sine wave acceleration IEC 60068-2-27 50 gn 11 ms) half sine wave acceleration IEC 60068-2-27
Mechanical robustness	Free fall resistance 1000 mm EN/IEC 60068-2-32
Communication port protocol	Zigbee green power 2.4 GHz
Maximum sensing distance	328.08 ft (100 m) in free field 82.02 ft (25 m) transmitter in the handy box and receiver in a metal enclosure 984.3 ft (300 m) transmitter in the handy box, receiver in metal enclosure and use relay-antenna
Acquisition time	2 ms
Response time	< 2 ms
Emission Power	3 mW

Environment

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Ambient Air Temperature for Storage	-40...158 °F (-40...70 °C)
Ambient Air Temperature for Operation	-13...131 °F (-25...55 °C)
IP degree of protection	IP65 IEC 60529 front face) IP65 UL Type 12 front face)
IK degree of protection	IK03 conforming to IEC 50102
Relative humidity	95 % 158 °F (70 °C) without condensation
Vibration resistance	5 gn (f= 11...500 Hz) conforming to IEC 60068-2-6 +/- 10 mm (f= 2...11 Hz) conforming to IEC 60068-2-6
Electromagnetic compatibility	Electrostatic discharge immunity test - test level: 8 kV (in free air (in insulating parts)) conforming to IEC 61000-4-2 Electrostatic discharge immunity test - test level: 4 kV (on contact (on metal parts)) conforming to IEC 61000-4-2 Susceptibility to electromagnetic fields - test level: 20 V/m (80...3000 MHz) conforming to IEC 61000-4-3 Susceptibility to electromagnetic fields - test level: 6 V/m (3000...6000 MHz, distance = 20 m) conforming to IEC 61000-4-3
Radio agreement	RSS UL 508 ARIB T66 CSA C22.2 No 14 ICASA ANATEL FCC
Standards	EN/IEC 60947-5-1 UL 508 EN/IEC 60947-1 CSA C22.2 No 14
Product Certifications	UL EAC CSA BT 2006/95/EC CCC C-tick
Directives	1999/5/EC - R&TTE directive 2004/108/EC - electromagnetic compatibility

Ordering and shipping details

Category	US1000I22470
Discount Schedule	000I
GTIN	3606480891113
Returnability	Yes
Country of origin	FR

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	2.677 in (6.800 cm)
Package 1 Width	2.677 in (6.800 cm)
Package 1 Length	6.575 in (16.700 cm)
Package weight(Lbs)	7.266 oz (206.000 g)

Contractual warranty

Warranty (in months)	18
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better

Materials and Substances	
Packaging without single use plastic	No
SCIP Number	25b7f895-3732-43c8-9910-ef6005058640
EU RoHS Directive	Compliant By Exemption
REACH Regulation	Reference contains Substances of Very High Concern above the threshold
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

Use Longer

Lifetime extension	
Repair	No
Product reparability index	A

Use Again


Repack and remanufacture	
Take-back	No

Dimensions Drawings

Dimensions

Wireless and Batteryless Pushbutton

Plastic Mobile Box for Mobile or Fix Use - 2 Functions



Technical Illustration

Dimensions

