



### Main

|                              |   |
|------------------------------|---|
| Device short name            | G   |
| Enclosure type               | Standard environment enclosure indoor                       |
| Factory modification         | 2-way pressure release valve                                |
| Product specific application | Control electrically driven water pumps and air compressors |
| Range of product             | Square D Pumptrol   |
| Switch application           | Standard  |

### Complementary

|                                     |  |
|-------------------------------------|--|
| Adjustable range on rising pressure | 65...200 psi (448.16...1378.95 kPa)  |
| Approximate adjustable differential | 20...40 psi (137.90...275.79 kPa)  |
| Depth                               | 3.68 in (93.47 mm)   |
| Electrical connection               | Screw clamp terminal   |
| Fixing mode                         | By brackets  |
| Fluid connection type               | 0.25 inch NPSF internal  |
| Height                              | 5.72 in (145.29 mm)  |
| Material                            | Zinc plated steel flange   |
| Materials in contact with fluid     | Nitrile (Buna-N) diaphragm   |
| Maximum pressure                    | 300 psig   |
| Maximum Horse Power Rating          | 2 Hp 115 V AC, 1 phase<br>3 Hp 115 V AC, 3 phase<br>3 Hp 230 V AC, 1 phase<br>5 Hp 230 V AC, 3 phase<br>5 Hp 460/575 V AC, 1 phase<br>5 hp 460/575 V AC, 3 phase |
| Number of poles                     | 2  |
| Permissible voltage                 | 575 V AC   |
| Pressure actuator                   | Diaphragm  |
| Pressure setting range              | 80...100 psi (551.58...689.48 kPa)   |
| Net Weight                          | 2.25 lb(US) (1.02 kg)  |
| Range on decreasing pressure        | 40...170 psi (275.79...1172.11 kPa)  |
| Switch function                     | DPST   |
| Maximum Width                       | 3.44 in (87.38 mm)   |

### Environment

|                           |  |
|---------------------------|--|
| NEMA degree of protection | NEMA 1   |
| Product certifications    | CSA file LR25490<br>UL listed file E12158 CCN NKPZ |

## Ordering and shipping details

|                       |   |
|-----------------------|---|
| Category              | 21536 - 9013 G COMMERCIAL PRESSURE SWITCH |
| Discount Schedule     | CP7G                                      |
| GTIN                  | 00785901560074                            |
| Nbr. of units in pkg. | 1   |
| Package weight(Lbs)   | 2.25 lb(US) (1.02 kg)                     |
| Returnability         | No  |
| Country of origin     | MX  |

## Packing Units

|                  |                      |
|------------------|----------------------|
| Package 1 Height | 12.40 in (31.484 cm) |
| Package 1 width  | 4.88 in (12.395 cm)  |
| Package 1 Length | 31.48 in (79.969 cm) |

## Offer Sustainability

|                            |   |
|----------------------------|---|
| Sustainable offer status   | Green Premium product   |
| California proposition 65  | WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a> |
| REACH Regulation           | <a href="#">REACH Declaration</a>   |
| EU RoHS Directive          | Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a>  |
| Mercury free               | Yes   |
| RoHS exemption information | <a href="#">Yes</a>   |
| Environmental Disclosure   | <a href="#">Product Environmental Profile</a>   |
| Circularity Profile        | <a href="#">End Of Life Information</a>   |

## Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|