



## Main

|              |                                |
|--------------|--------------------------------|
| Product Type | Industrial Control Transformer |
| Type         | T                              |

## Complementary

|                                |  |
|--------------------------------|--|
| Number of Phases               | 1 phase  |
| Power Rating                   | 250 VA UL<br>250 VA CSA<br>250 VA NOM<br>160 VA CE |
| Primary to Secondary Voltage   | 208 V 24 V   |
| Temperature Rise               | 80 °C  |
| Electrical Connection          | Screw clamp terminals                              |
| Height                         | 3.2 in (81.28 mm)                                  |
| Width                          | 3.75 in (95.25 mm)                                 |
| Depth                          | 5.3 in (134.62 mm)                                 |
| Material                       | Copper: winding                                    |
| Fingersafe Cover Compatibility | FSC2   |

## Environment

|                        |  |
|------------------------|--|
| Certifications         | UL listed file E61239[RETURN]CSA file LR37055 guide 184-N-90 |
| Enclosure Type         | Not rated (open device)                                      |
| Insulation Temperature | 266 °F (130 °C)  |

## Ordering and shipping details

|                   |                                  |
|-------------------|----------------------------------|
| Category          | 16201-9070 T (NOT TF) 250-2000VA |
| Discount Schedule | CP8                              |
| GTIN              | 785901338628                     |
| Returnability     | Yes                              |
| Country of origin | US                               |

## Packing Units

|                              |                       |
|------------------------------|-----------------------|
| Unit Type of Package 1       | PCE                   |
| Number of Units in Package 1 | 1                     |
| Package 1 Height             | 5.60 in (14.22 cm)    |
| Package 1 Width              | 6.20 in (15.75 cm)    |
| Package 1 Length             | 7.40 in (18.8 cm)     |
| Package 1 Weight             | 7.96 lb(US) (3.61 kg) |

## Offer Sustainability

|                            |   |
|----------------------------|---|
| Sustainable offer status   | Green Premium product   |
| California proposition 65  | WARNING: This product can expose you to chemicals including: Phenyl glycidyl ether, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a> |
| REACH Regulation           | <a href="#">REACH Declaration</a>   |
| EU RoHS Directive          | Compliant with Exemptions   |
| Mercury free               | Yes   |
| China RoHS Regulation      | <a href="#">China RoHS Declaration</a>  |
| RoHS exemption information | <a href="#">Yes</a>   |
| Environmental Disclosure   | <a href="#">Product Environmental Profile</a>   |
| Circularity Profile        | No need of specific recycling operations  |
| PVC free                   | Yes   |

## Contractual warranty

|          |          |
|----------|----------|
| Warranty | 10 Years |
|----------|----------|