



Aluminum Drain, 1/2" NPT - Ex e Class I Div. 2 IP66/4X

By Killark
Catalog # [KDEAL0050](#)

Aluminum Drain, 1/2" NPT - Ex e Class I Div. 2 IP66/4X



*Representative Image

Features

- Silicone O-ring supplied as standard and suitable for use in a -55°C to +80°C temperature range.
- Aluminum.
- Internal 316 stainless steel locknut supplied as standard.
- When tightened to the proper torque the joint makes a hose down tight seal for type 4, 4X & IP66 application.

General

Catalog Number	KDEAL0050
EU RoHS Indicator	Contact Manufacturer
Material	Aluminum, Copper Free (less than 4/10 of 1%)
Operating Temperature Celcius Max	80
Operating Temperature Celcius Min	-55 °C
Operating Temperature Range Celcius	-55°C to 80°C
Series	KDE
UPC	783936121598

Dimensions

Hub Size	1/2"
----------	------

Certifications And Compliance

ATEX File Number	15ATEX3028X
CSA File Number	2715851
Hazardous Rating(s)	<ul style="list-style-type: none"> • Class I, Divisions 2, Groups A, B, C, D • Class I, Zones 1 & 2 • Class II, Divisions 1 & 2, Groups E, F, G • Class III, Divisions 1 & 2
IECEx File Number	15.0002X
Nema Rating	3, 4, 4X

Logistics

Carton Quantity	10
-----------------	----

Product Assets

- [Catalogs - Killark Catalog](#)
- [Certifications - KDE Series CSA Certification](#)
- [Certifications - KDE Series Drain Breathers IECEx Certification](#)
- [Certifications - KDE Series ATEX Certificate](#)
- [Certifications - KDE Series Declaration of Conformity](#)
- [Customer Notices - Prop 65 Notice](#)
- [Installation Manuals - KDE Series IOM K1458](#)
- [Specifications - KDEAL0050 Specification Sheet French](#)
- [Specifications - KB Series Drain, Breathers, & Flame Arrestors Specification Sheet](#)
- [Specifications - KDE Series Drain Breathers Specification Sheet](#)
- [Specifications - KDEAL0050 Specification Sheet English](#)