

# Product Datasheet

## Characteristic

# 3090SCCT022

Square D - PowerLogic 3090 SCCT -  
split core CT - 200/5 A - size 2 - 2.5 VA



## Main

range	PowerLogic
product or component type	Current transformer
accessory / separate part category	Measurement accessory

## Complementary

range compatibility	Powerlogic PowerLogic PM5000 power meter Powerlogic PowerLogic PM3000 power meter Powerlogic PowerLogic PM8000 power meter Powerlogic PowerLogic ION7400 power meter Powerlogic CM4000T circuit monitor Acti 9 Acti 9 iEM3000 energy meter
current transformer type	Split core
primary operational current	200 A
secondary current	5 A
network type	AC
network frequency	50/60 Hz
current transformer ratio	200/5
secondary power	2.5 VA
electrical connection	5.91 ft (1.8 m)
insulation	Basic insulation: 600 V AC Reinforced insulation: 300 V AC
measurement accuracy	1 % full scale
mounting location	Indoor use only
width	1.26 in (32 mm) 4.76 in (121 mm)
depth	1.14 in (29 mm)
height	1.5 in (38 mm) 4.21 in (107 mm)

## Environment

relative humidity	0...95 % non-condensing
installation category	III
pollution degree	2
ambient air temperature for operation	5...140 °F (-15...60 °C)
ambient air temperature for storage	-40...158 °F (-40...70 °C)

---

operating altitude	<= 9842.52 ft (3000 m)
standards	IEC 61010-1 UL 61010-1 UL 1015

---